

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 10

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8518)

Set a Fir post, 3 ft. long, 4" sq., 24" in the ground for ¼ sec. corner, marked ¼ S on W. face; from which
A Fir 16" dia., bears N.63°E., 67 lks. mkd. ¼ S BT.
A Fir 36" dia., bears N.18°W., 102 lks. mkd. ¼ S BT.
This corner is on the N. slope of spur, 350 ft. below top.

GLO resurvey by Hans W. Thielsen, under Group #'s 350 & 422, Surveyed, May/June 1959 - (DCSO records Vol. 30 Page(s) 12781)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 20" in the ground, with brass cap mkd: ¼
S 9|S 10
T32S R4W
1959

from which
A Fir 10" dia., bears S.9°E., 63 lks. mkd. ¼ S10 BT.
A Fir 16" dia., bears S.34½°W., 72 lks. mkd. ¼ S9 BT.

Tony Hostetter - For: Seneca Jones Timber Co. Co. - April 2006 - M150-60

Found - 1959 BLM brass cap as described by Thielsen (Vol 20, PG 12782 from which:
30" hemlock, face evident, BLM tag, bears S.37°W, 47.5 ft. (S.34½° (W) 72 lks)
New BTs- 10" madrone, scribed "S10 ¼ BT", bears N.23°19'E., 21.5 ft to spike.
12" fir, scribed "S10 ¼ BT" bears N74°36'E., 20.2 ft to spike.
15" fir, scribed "S9 ¼ BT" bears S51°40'W., 37.5 ft to spike.