

PRIMARY CORNER DESCRIPTION C C cor. Secs. 3 & 4 only, T33-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Edward F. Sharp, Deputy Surveyor, under Contract #617, dated June 3, 1893 (DCSO records Vol. 21 Page(s) 8932)

The closing cor. to secs. 3 and 4, I set a basaltic stone, 14 x 10 x 12 ins., 10" in the ground, marked C C with 3 notches on E. and W. edges, from which

A Fir 12" dia., bears S.63°15'E., 137 lks. dist., marked T33S R4W S3 BT.

A Fir 4 ft. dia., bears S.89°W., 80 lks. dist., marked T33S R4W S3 BT.

A Fir 12" dia., bears N.55°30'E., 111 lks. dist., marked T33S R4W C C S3 and 4 BT.

This cor. is 300 ft. above creek at 42.53 chs.

BLM resurvey by Lynn M. Roseberry and Rollin D. Aanrud, Cadastral Surveyors, Under Group #865, surveyed July/Oct. 1975 (DCSO records Vol. 42 Page(s) 16520)

The true point for the closing corner of secs. 3 and 4, located in graveled road, 30 lks. wide, bears N.20°W., and N.20°E.

Set an iron post 28" long, 2½" dia., 32" in the ground, the top 4" below surface of the road, with brass cap mkd:

T 32 S
S 34
S 4 | S 3
C C
T 33 S R 4 W
1975

from which

A Fir 10" dia., bears S.13°E., 64 lks. dist., mkd. T33S R4W S3 CC BT.

A Fir 7" dia., bears S.88½°W., 20 lks. dist., mkd. T33S R4W S4 CC BT.

From this point, the original closing cor. of sec. 3 and 4, bears N.0°42'E., 0.045 chs. dist., determined at record bearing and distance from the remains of the original bearing trees:

A Fir root crown, size indeterminate bears N.55½°E., 111 lks. dist., no marks visible.

A root hole bears S.63¾°E., 137 lks. dist.

A burned Fir stump 38" dia., bears S.89°W., 80 lks. dist., with burned blaze.

continued next page

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 406100

PRIMARY CORNER DESCRIPTION C C cor. Secs. 3 & 4 only, T33-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Harvey M. Christensen - For: Future Logging Co. & Silver Butte Timber Co. - Feb. 2024 - M183-61

Found - 2.5' BLM BC CC, 0.4' below grade in road, 1975.
BTs - 9" D.Fir, S.73°E., 74.5 ft. blazed & scribed "T33S
R4W S3 BT"
21' D.Fir N.66°E. 39.4 ft blazed & scribed "X" "BT"
24" D.Fir S.88.5°W., 13.2 ft. partly healed face
28" D.Fir, S.13°E., 42.2 ft. partly healed face.