

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 432600

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. Sec. 10 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Hans W. Thielsen, under Group #'s 350 & 422, Surveyed, May/June 1959 - (DCSO records Vol. 20 Page(s) 12782)

Point for the ¼ sec. cor. of sec. 10, at midpoint between the closing cor. of secs. 9 and 10, and the closing cor. of secs. 3 and 10.

Set an iron post, 28" long, 2 1/2" dia., 20" in the ground, with brass cap mkd:

¼ S 10
T32S R4W
1959

from which

A Madrona 6" dia., bears S.72°E., 28 lks. mkd. ¼ S10 BT.

A Fir 10" dia., bears S.57½°W., 10 lks. mkd. ¼ S10 BT.

Tony Hostetter - For: Seneca Jones Timber Co. Co. - April 2006 - M150-60

Found - 1959 BLM brass cap as described by Thielsen (Vol 30, pg 12782) from which:

11" madrone, BLM tag, bears S.72°E, 18.5 ft.

16" fir, face evident, bears S.57½°(W), 6.6 ft.

New BTs- 21" fir. scribed "S10 ¼ BT bears S.12°W., 3.4 ft to spike.

10" Madrone, scribed S10 ¼ BT bears N.12°W., 14.9 ft to spike.