

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 440200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 27 and 34

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8469-70)

Set a basalt stone 14 x 12 x 8 ins., 9" in the ground, for ¼ sec. corner, mkd. ¼ on N. face, from which
A Fir 8" dia., bears S.63°E., 14 lks. mkd. ¼ S BT.
A Fir 10" dia., bears N.18°W., 20 lks. mkd. ¼ S BT.

Douglas Co. Surveyors Office - John M. Powell - May 18, 1970 (added 9/4/2019) - C.S. File 54/114-32

Not Found
found old E-W blazes, also old trail blazes which a call of 39 chain was given on
2 small firs, 8" - 10", a lot of rot in this area, also seems some stones were moved where someone else was looking for cor

Survey by Mark E. Boyden L.S. #281 - For: Boise Cascade Corp. July 26, 1976 - C.S. File 58/112 and M 61-7

Diligent search was made for original ¼ corner with negative results.
Set by proportionate measurement, a 3/4" x 36" galv. I.P. with 2" brass cap stamped T32SR4W ¼ 27 cor. 1976 exposed 6".
34
New BTs -Scribed an 8" D.Fir "¼S-BT" which bears N.80°E., 3.8 ft. to the face of the lower blaze.
Scribed an 8" D.Fir "¼S-BT" which bears S.45½°E., 5.6 ft. to the face of the lower blaze.

Fd. BC, July 1990, M 110-28