

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 22 and 27

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8511)

A Madrona 10" dia., I mark ¼ S. on N. side, from which
A Madrona 8" dia., bears N.27°E., 40 lks. mkd. ¼ S BT.
A Fir 20" dia., bears S.29°E., 16 lks. mkd. ¼ S BT.
This ¼ sec. cor. is on the SW slope, 100 ft. below top.

GLO remonumentation by Hans W. Thielsen, under Group #'s 350 & 422, Surveyed, May/June 1959 - (DCSO records Vol. 30 Page(s) 12797)

The ¼ sec. cor., determined at record bearing and distance from the remaining original bearing tree:

A Fir 34" dia., bears S.29°E., 16 lks. mkd. with a healed blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 20" in the ground, with brass cap mkd:

¼ S 22
S 27
T32S R4W
1959

from which a new bearing tree:

A Fir 8" dia., bears N.65°W., 111 lks., mkd. ¼ S22 BT

Greg Lang, July 1995, M 122-46

Mon. Fd. - B.Cap on the N.E. side of Laurel
BT's Fd. - 31½" fir snag, bears S.29°E., 16 lks. (rec.)
(location tag says N.30°W., 9.5')
(measured bearing S.20°E., 8.6')

David Edwards - For: Seneca Jones Timber Co. & Plum Creek Timberlands - 11/2010 - M161-51

Found - Brass cap
New BTs- 9" Fir bears S.53°E., 3.2 ft. scribed "¼ S22 BT"
9" Fir bears N.53°W., 10.8 ft. scribed "¼ S15 BT"
Set - 6 ft. steel post 2 ft. East.