

TOWNSHIP 32 RANGE 02 POINT IDENTIFIER # 440400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 15 & 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Charles L. Campbell, Deputy Surveyor, under Contract #747 dated May 5, 1902 - (DCSO records Vol. 20 Page(s) 8321

Set an ironstone 24x12x6", 18" in the ground for ¼ sec. cor. mkd. ¼ on N face, from which
A fir, 60" dia., bears S.29°E., 56 lks., mkd: ¼ S22 BT.
A fir, 44" dia., bears N.23°W., 60 lks., mkd: ¼ S15 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Vincent Perron - 7/23/1970 - C.S. File 54/117-2

Found - Corner Stone, as called for, in place, mkd: "¼" on N. face.
Orig. 60" Fir, now 64" Fir Stump, S.29°E. 37.0 ft., shows good axe scar.
Orig. 44", now 48" Fir, turned out, N.23°W. 39.6 ft., scribe visible on previously opened blaze.
Set - Brass Cap at Cor. Mkd: County Surveyors T32S R2W
(Reset Stone alongside) Office ¼ S 15
1970 S 22
New BTs- 12" R.Fir N.27°E., 33.9 ft. mkd: "¼ S15 CS BT".
14" R.Fir S.69°E., 70.2 ft. mkd: "¼ S22 CS BT".
This corner lies on moderate northerly slope in old logged unit.