

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 15

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8516)

Set a Fir post, 3 ft. long, 4" sq., 24" in the ground for ¼ sec. corner, marked ¼ S on N. face; from which
A dead Fir 12" dia., bears S.49°E., 73 lks. mkd. ¼ S BT.
A dead Fir 48" dia., bears N.73°W., 60 lks. mkd. ¼ S BT.
This corner is on the W. slope of spur, 50 ft. below top.

GLO resurvey by Hans W. Thielsen, under Group #'s 350 & 422, Surveyed, May/June 1959 - (DCSO records Vol. 30 Page(s) 12780)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 20" in the ground, with brass cap mkd:
¼ S 10
S 15
T32S R4W
1959

from which
A Fir 6" dia., bears N.2¼°W., 49 lks. mkd. ¼ S10 BT.
A Fir 8" dia., bears S.48 3/4°E., 22 lks. mkd. ¼ S15 BT.