

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 3; and Sec. 34, T31-4

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 18 Page(s) 7784)

Set ¼ sec. post, from which
A Laurel 10" dia., bears N.50°W., 9 lks. dist.
A Fir 20" dia., bears South, 45 lks. dist.

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8507-08)

The ¼ sec. cor. post destroyed; bearing trees standing, from which I reestablish this ¼ sec. corner as follows:
Set a Madrona post, 3 ft. long, 4" sq., 24" in the ground for ¼ sec. corner, marked ¼ S. on N. face, from which
A Madrona 10" dia., bears N.50°W., 9 lks. dist. mkd. ¼ SBT.
A Fir 20" dia., bears South, 45 lks. mkd. ¼ S BT.

GLO remonumentation by Hans W. Thielsen, under Group #'s 350 & 422, Surveyed, May/June 1959 - (DCSO records Vol. 30 Page(s) 12788)

The ¼ sec. cor., determined at record bearing and distance from each of the original bearing trees:
A Madrona 12" dia., bears N.50°W., 9 lks. dist., mkd. ¼ S on opened blaze.
A Fir 44" dia., bears South, 45 lks. dist., marked ¼ S3 BT on opened blaze.

At the corner point
Set an iron post, 28 ins. long, 2 1/2 ins. dia., 20 ins. in the ground, with brass cap marked

T31S
¼ S 34
S 3
T32S R4W
1959

from which new bearing trees
A Fir 22" dia., bears N.42°E., 37 lks. dist., mkd. ¼ S34 BT.
A Fir 20" dia., bears S.25°E., 48 lks. dist., mkd. ¼ S3 BT.

Cor. Fd. and used in BLM resurvey by Roseberry and Evans, Group #778, surveyed July/Sept. 1972 (DCSO records, Vol. 38 Pages 15465-66)

Fd ok by Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - 5/27/1998 - C.S. File 66/4-12