

PRIMARY CORNER DESCRIPTION C C for 3 and 10; (on W.bdy. Sec. 11)

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

<p>GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8506)</p> <p>-----</p> <p>At a point of intersection, 8.30 chs South of NW cor. Sec. 11 Set a Fir post 3 ft. long, 4" sq., 24" in the ground for a closing corner of secs. 3 and 10, marked C. C. T32S R4W on W; S3 on N; & S10 on S; with 5 grooves on S face; from which</p> <p style="padding-left: 40px;">A Fir 6" dia., bears N.35°W., 55 lks. mkd. T32S R4W S3 BT.</p> <p style="padding-left: 40px;">A Fir 36" dia. bears S.75°W., 139 lks mkd. T32S R4W S10 BT</p> <p>This closing cor is on the S slope of spur, 20 ft above creek</p>
<p>GLO remonumentation by Hans W. Thielsen, under Group #'s 350 & 422, Surveyed, May/June 1959 - (DCSO recs Vol. 30 Pg 12783)</p> <p>-----</p> <p>Point for the closing cor. of secs. 3 & 10, at proportionate dist; there is no remaining evidence of the original corner. Set an iron post, 28" long, 2 1/2" dia., 20" in the ground, with brass cap mkd:</p> <p style="padding-left: 100px;">T32S R4W</p> <p style="padding-left: 100px;">C C $\frac{S\ 3}{S\ 10}$ S 11</p> <p style="padding-left: 150px;">1959</p> <p>from which</p> <p style="padding-left: 40px;">A Fir 7" dia. bears N.63½°W. 39 lks mkd. T32S R4W S3 CC BT</p> <p style="padding-left: 40px;">A Fir 5" dia. bears S.45°W., 7 lks mkd. T32S R4W S10 CC BT</p> <p>From this point, the NW cor. of sec. 11 bears N.0°11'E., 8.23 chs. dist.</p>
<p>Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - 5/21/1998 - C.S. File 66/2-39</p> <p>-----</p> <p>Condition report only</p> <p>Found - 3½" dia., brass cap an iron pipe is found under a large rotted down D.Fir, cap is flush with the ground & properly marked.</p> <p style="padding-left: 40px;">7" now 19" dia., D.Fir w/fully healed single blaze, bears N.63½°W., 25.7 ft. Agrees w/rec. 1959</p> <p style="padding-left: 40px;">5" now 10" dia., D.Fir w/fully healed single blaze, bears S.55°W., 4.6 ft. (Rec. S.45°W., 4.6') 1959</p>
<p>Tony Hostetter - For: Seneca Jones Timber Co. Co. - April 2006 - M150-60</p> <p>-----</p> <p>Found - 1959 BLM brass cap & both BTs as described by Smith</p> <p>New BT - 14" Fir scribed "S3 SE BT" bears N.82°22'W., 42.7 ft. to spike.</p>