

PRIMARY CORNER DESCRIPTION NW corner Section 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8500)

Set a Fir post 3 ft. long, for a temp. corner of secs. 2, 3, 10 and 11, 100 ft. below top of spur.

(Same surveyor, Pages 8505-06)

Set a Fir post, 3 ft. long, 4" sq., 24" in the ground, for NW. corner of Sec. 11, marked T32S S3 on NE.; R4W S11 on SE.; S3 on SW.; and S3 on NW. faces, with 2 notches on E. and 5 notches on S. edges; from which

A Fir 24" dia., bears S.48°E., 63 lks. mkd. T32S R4W S11 BT.

(Corner is N.0°2'E., 8.30 chs. from CC Secs. 3 and 10)

GLO remonumentation by Hans W. Thielsen, under Group #'s 350 & 422, Surveyed, May/June 1959 - (DCSO records Vol. 30 Page(s) 12779-80)

The NW. cor. of sec. 11, determined at record bearing and distance from the original bearing tree:

A fallen Fir 30" dia., bears S.48°E., 63 lks. marked with a healed blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 20" in the ground, with brass cap mkd:

T32S R4W
S 3

|S 11
1959

from which a new bearing tree

A Fir 36" dia., bears S.15 3/4°E., 61 lks. mkd. T32S R4W S11 BT.

Douglas Co. Surveyors Office - Randall W. Smith - Stephen J. Flause - 5/27/1998 - C.S. File 66/2-40

Found - 3 1/4" dia., brass cap on a 2 1/2" O.D. iron pipe, 1" below ground, properly marked. - BC/IP leans approx. 12" Northerly of plumb.

36" now 37" dia., 4 1/2' high D.Fir stump with a fully healed single blaze bears S.15 3/4°E., 40.3'. Stump is solid. Agrees with rec. 1959

Found BC/IP returned to plumb position, now protrudes 4" above ground.

(Cont. next page)

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 474600

PRIMARY CORNER DESCRIPTION NW Cor. Sec. 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BTs- 5" dia., D.Fir, double blazed and scribed "NW S11 CS BT" bears S.29½°E., 15.4'.
Double trunked D.Fir, double blazed and scribed "X CS BT" on 5" dia., westerly trunk, root crown bears S.81°W., 2.5'.
Corner lies 6' south of the top of steep road cut bank on a steep north slope.

Found OK by R. Wytcherley, Feb. 2004 - M143-76