

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 500140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 34 and 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8490)

Set a basalt stone 12 x 10 x 8 ins., 8" in the ground, for ¼ sec. cor., mkd. ¼ on W. face; from which
A Fir 8" dia., bears N.20°E., 47 lks. mkd. ¼ S BT.
A Fir 14" dia., bears N.21°W., 30 lks. mkd. ¼ S BT.
This cor. is on the SW. slope of mountain 50 ft. below top.

Douglas Co. Surveyors Office - John M. Powell, J. Heritage, W. Penley, crew - May 18, 1970 - C.S. File 54/114-31

Found - 12x10x8 stone at ¼ cor. mkd. "¼" on West face.
8" D.Fir, rotted stump, N.20°E., 31.0 ft. found scribe "S B"
14" now 23" D.Fir N.21°W., 19.8 ft., shows scar.
Set Brass cap at cor. mkd: County Surveyors Office
D T 32 S R 4 W J
O ¼ S 34 | S 35 A
U 1970 C
G K
CO. CO.
New BT - 16" D.Fir S.87°E., 33.0 ft.
Good call on ridge top, approx. 90 ft. S. of said high ridge.

Fd. and used in BLM resurvey by Roseberry and Aanrud, Group #865, surveyed July/Oct. 1975 (DCSO records, Vol. 42 Page 16543)

Fd. OK, July 1990, M 110-28