

PRIMARY CORNER DESCRIPTION Sec. Cor. for 26, 27, 34 and 35

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8468-69)

-----  
Set a basalt stone 14 x 8 x 6 ins., 9" in the ground for cor. of secs. 26, 35, 34 and 27, mkd. with 2 notches on E. and 4 notches on W. edges; from which  
A Fir 10" dia. bears N.87°E., 42 lks. mkd. T32S R4W S26 BT  
A Fir 10" dia. bears S.60°E., 27 lks. mkd. T32S R4W S35 BT  
A Cedar 14" dia. bears S.32°W. 25 lks. mkd. T32S R4W S34BT  
A Fir 12" dia. bears N.65°W., 31 lks. mkd. T32S R4W S27 BT  
This corner is on the NE slope of ridge, 50 ft. above ravine.

GLO resurvey by Hans W. Thielsen, under Group #'s 350 & 422, Surveyed, May/June 1959 - (DCSO records Vol. 30 Page(s) 12794)

-----  
The sec. cor., determined at record bearing and distance from the remaining original bearing tree:  
A Cedar 20" dia., bears S.32°W., 25 lks. dist., mkd. with portions of scribed marks on open blaze.  
At the corner point  
Set an iron post, 28" long, 2½" dia., 20" in the ground, with brass cap mkd:  
T32 S R4W  
S 27 S 26  
S 34 S 35  
1959  
from which new bearing trees  
A Fir 14" dia. bears N.29½°E., 116 lks. mkd. T32S R4W S26 BT.  
A Fir 14" dia. bears S.71°E., 113 lks. mkd. T32S R4W S35BT  
A Fir 26" dia., bears S.3°W., 80 lks. mkd. T32S R4W S34 BT  
A Fir 5" dia., bears N.81°W., 38 lks. mkd. T32S R4W S27 BT

Bruce Shaner - For: Seneca Jones Timber Co. - July 2002 - M140-41 & C.S. File 65/44-7A

-----  
Found - 2½" iron pipe with 3¼" brass cap (properly mkd.)  
26" D.Fir, face overgrown, bears N.29½°E., 76.6 ft.  
36" D.Fir, face overgrown, bears S.71°E., 74.6 ft.  
36" D.Fir, stump, face overgrown, bears S.3°W., 49.6 ft. (rec. 52.8 ft.)  
18" D.Fir, face overgrown, now blown down, but stump in ground, bears N.81°W., 25.1 ft.  
New - 6 ft. steel fence post bears N.3°W., 1.0 ft.  
6 ft. steel fence post bears East, 1.0 ft.