

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 27

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8491-92)

Set a basalt stone 14 x 10 x 8 ins. 9" in the ground for ¼ sec. corner, mkd. ¼ on N. face; from which
A Fir 24" dia., bears N.34°E., 42 lks. mkd. ¼ S BT.
A Fir 36" dia., bears N.67°W., 32 lks. mkd. ¼ S BT.

GLO remonumentation by Hans W. Thielsen, under Group #'s 350 & 422, Surveyed, May/June 1959 - (DCSO records Vol. 30 Page(s) 12794-95)

The ¼ sec. cor., monumented with a basalt stone, 14x10x8 ins., mkd. ¼ on N. face, from which the original bearing trees:

- A sawed Fir stump 26" dia., bears N.34°E., 42 lks. mkd. with portions of scribed marks on opened blaze.
- A Fir snag 40" dia., bears N.67°W., 32 lks. mkd. with a healed blaze.

At the corner point

Set an iron post, 28" long, 2½" dia., 20" in the ground, with brass cap mkd: ¼

S 27 S 26
T32S R4W
1959

from which new bearing trees

- A Fir 36" dia., bears N.45°W., 119 lks. mkd. ¼ S27 BT
- A Fir 22" dia., bears S.8°W., 179 lks. mkd. ¼ S27 BT.

No suitable tree is available in sec. 26.

Deposit basalt stone alongside iron post.

Bruce Shaner - For: Seneca Jones Timber Co. - July 2002 - M140-41 & C.S. File 65/44-7B

Found - 2½" IP with 3¼" brass cap (properly mkd.) from which:
Orig. corner, 14"x10"x8" basalt stone, sets South 1.0 ft.

36" D.Fir, face overgrown, bears S.2°W., 112.0 ft. (rec. 118.1 ft.)

40" D.Fir stump, was snag, bears N.67°W., 20.1 ft to face.

New - 10" D.Fir, scribed "¼ S27 BT" bears S.52°W. 19.2 ft.

8" D.Fir scribed "¼ S26 BT" bears S.52°E., 10.4 ft.

6 ft. steel fence post bears North, 1.0 ft.