

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 26 and 27

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8492)

-----  
Set a basalt stone 14 x 10 x 8 ins., 9" in the ground for corner of secs. 22, 23, 26 and 27, marked with 2 notches on S. and E. edges; from which

- A Cedar 24" dia., bears N.42½°E., 49 lks. mkd. T32S R4W S23 BT.
- A Fir 20" dia., bears S.29°E., 44 lks. mkd. T32S R4W S26 BT.
- A Cedar 14" dia., bears S.72°W., 41 lks. mkd. T32S R4W S27 BT.
- A Fir 30" dia., bears N.51°W., 61 lks. mkd. T32S R4W S22 BT.

This corner is near the bottom of ravine, sloping N.70°W., 150 ft. below top of ridge.

H.L. Eppstein, Co. Surveyor - by Bert A. Lane - For: Clare Lumber Co. - July 1937 - C.S. File 15/25 and M 6-6 (and "old" corner book, page 170)

-----  
Set Post from old BT. BT in good shape except tree in SE quadrant down.

Marked new BT:

- A 30" Fir S.13°E., 24½ ft. "S27 CS BT".

GLO remonumentation by Hans W. Thielsen, under Group #'s 350 & 422, Surveyed, May/June 1959 - (DCSO records Vol. 30 Page(s) 12795)

-----  
The Sec. cor., determined at record distance from each of the remaining original bearing trees:

- A Cedar 32" dia., bears N.22½°E., 49 lks. mkd. with portions of scribed marks on opened blaze. (Rec. bearing N.42½°E.)
- A Cedar 20" dia., bears S.72°W., 41 lks. mkd. with an opened blaze.
- A sawed Fir stump 40" dia., bears N.57°W., 61 lks. mkd. with a healed blaze. (Rec. bearing N.51°W.)

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 20" in the ground, with brass cap mkd:

T32S R4W
S 22   S 23
S 27   S 26
1959

from which new bearing trees

(Cont. Next Page)

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 26 and 27

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

A Cedar 32" dia. bears S.5°E. 79 lks. mkd. T32S R4W S26 BT  
A Fir 50" dia. bears N.49°W. 98 lks. mkd. T32S R4W S22 BT.

Fd. OK, G. Nygren, Nov. 1989, C.S. File 63/51

Bruce Shaner - For: Seneca Jones Timber Co. - July 2002 -  
M140-41 & C.S. File 65/44-7C

-----  
Found - BLM 2½" IP w/3¼" brass cap, properly mkd. from which  
38" Cedar, face overgrown, orig. BT, bears N.46°E.,  
(rec. N.42¼°E.) 32.3 ft.  
28" Cedar, face overgrown, bears S.72°W., 27.3 ft.  
40" D.Fir stump, face overgrown, bears N.57°W., 39.0  
ft. (rec. 40.3 ft.)  
40" Cedar, face overgrown, bears S.7°W., (rec.  
S.5°E.) 52.1 ft.  
50" D.Fir stump bark scribes visible, bears N.49°W.,  
64.7 ft.  
New - 12" D.Fir, scribed "T32S R4W S26 BT" bears S.48°E.,  
28.7 ft.  
6 ft. steel fence post bears East, 1.0 ft.  
6 ft. steel fence post bears South, 1.0 ft.  
Note - Corner is located 380 ft. west of rock logging road.

Fd. cor. as per C.S. File 65/44-7: by D. Edwards 11/2010 -  
M161-51