

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 500440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 14 and 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8496)

Set a basalt stone 14 x 12 x 8 ins., 9" in the ground for ¼ sec. corner, marked ¼ on W. face; from which
 A Fir 16" dia., bears N.81°W., 61 lks. mkd. ¼ S BT.
 A Fir 12" dia., bears S.47°E., 13 lks. mkd. ¼ S BT.
This corner is on the S. slope of mountain, 300 ft. above creek.

Survey by Richard L. Templin, Jr. - For: So. Oregon Plywood Corp. - April/May 1956 - C.S. File 42/159

Found - Stone marker and scribed the following new BT:
 28" D.Fir S.78°E., 21.0 ft. marked ¼S 14 BT RE3024.

GLO remonumentation by Hans W. Thielsen, under Group #'s 350 & 422, Surveyed, May/June 1959 - (DCSO records Vol. 30 Page(s) 12797)

The ¼ sec. cor., monumented with a basalt stone, 14x12x8 ins., marked ¼ on N. face.
At the corner point
Set an iron post, 28" long, 2 1/2" dia., 20" in the ground, with brass cap mkd: ¼
 S 15 S 14
 T32S R4W
 1959
from which
 A Fir 8" dia., bears N.61°E., 20 lks. mkd. ¼ S14 BT.
 A Fir 8" dia., bears N.50½°W., 32 lks. mkd. ¼ S15 BT.
Deposit basalt stone alongside iron post.