

PRIMARY CORNER DESCRIPTION Sec. Cor. for 10, 11, 14 and 15

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8496)

Set a basalt stone 12 x 10 x 7 ins., 8" in the ground for corner of secs. 10, 11, 14 and 15, marked with 2 notches on E. and 4 notches on S. edges, from which
A dead Fir 24" dia., bears N.31°E., 78 lks. marked T32S R4W S11 BT.
A dead Fir 24" dia., bears S.72°E., 49 lks. marked T32S R4W S14 BT.
A dead Fir 20" dia., bears S.56°W., 70 lks. marked T32S R4W S15 BT.
A dead Fir 20" dia., bears N.5°W., 114 lks. marked T32S R4W S10 BT.
This corner is about 75 ft. below top of ridge.

Survey by Richard L. Templin, Jr. - For: So. Oregon Plywood Corp. - April/May 1956 - C.S. File 42/159

The locus of this corner was determined from the intersection of original blazed section lines ascertained by ring count and from the rotted stumps of the four original bearing trees with no marks discernable:
Rotted stump, 24" D.Fir bears N.31°E., 50.5 ft.
Rotted stump, 24" D.Fir bears S.72°E., 32.0 ft.
Rotted stump, 20" D.Fir bears S.56°W., 45.1 ft.
Rotted stump, 20" D.Fir bears N.5°W., 72.4 ft.
I was unable to find the rock after a diligent search.

I placed a mound of stone to monument the corner, from which bears the following new witness trees:
5" D.Fir bears S.24°W., 10.9 ft. marked S15 BT RE3024
7" D.Fir bears N.24°W., 32.0 ft. marked S10 BT RE3024
6" D.Fir bears N.26°E., 44.0 ft. marked S11 BT RE3024
10" D.Fir bears S.3°E., 54.4 ft. marked S14 BT RE3024

GLO resurvey by Hans W. Thielsen, under Group #'s 350 & 422, Surveyed, May/June 1959 - (DCSO records Vol. 30 Page(s) 12778-79)

The Sec. cor., determined at record bearing and distance from the remaining original bearing trees:
A sawed Fir stump 24" dia., bears N.31°E., 78 lks. marked BT on opened blaze.
A rotted Fir stump 24" dia., bears S.72°E., 49 lks. no marks remaining.
At the corner point

(Cont. Next Page)

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 10, 11, 14 and 15

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Set an iron post, 28" long, 2 1/2" dia., 14" in the ground to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd:

T32S R4W
S 10 S 11
S 15 S 14
1959

from which new bearing trees

- A Fir 6" dia., bears N.26°E., 67 lks. mkd. T32S R4W S11 BT
- A Fir 10" dia., bears S.3°E., 82 lks. mkd. T32S R4W S14 BT
- A Fir 5" dia., bears S.24°W., 17 lks. mkd. T32S R4W S15 BT
- A Fir 7" dia., bears N.24°W., 49 lks. mkd. T32S R4W S10 BT