

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 500540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 10 and 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8499)

Set a Fir post, 3 ft. long, 4" sq., 24" in the ground for ¼ sec. corner marked ¼ S on W. face; from which
A Madrona 6" dia., bears N.36°E., 6 lks. mkd. ¼ S BT.
A Madrona 8" dia., bears S.32°W., 18 lks. mkd. ¼ S BT.
This corner is on the S. slope of mountain, 100 ft. above creek.

GLO remonumentation by Hans W. Thielsen, under Group #'s 350 & 422, Surveyed, May/June 1959 - (DCSO records Vol. 30 Page(s) 12779)

Point for the ¼ sec. cor. of secs. 10 and 11, at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 20" in the ground, with brass cap mkd: ¼
S 10 S 11
T32S R4W
1959
from which
A Fir 8" dia., bears S.52½°E., 3 lks. mkd. ¼ S11 BT.
A Madrona 8" dia., bears West, 20 lks. mkd. ¼ S10 BT.