

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 528100

PRIMARY CORNER DESCRIPTION A.P. #2, S. bdy. Sec. 35

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

NOT IN DOUGLAS COUNTY

GLO survey by McKenzie and Eckelson, Deputy Surveyor, under Contract #328, dated June 17, 1879 (DCSO records Vol. 20 Page(s) 8464)

Set post for corner to secs. 34 & 35, from which,
A Fir, 18" dia, N.40°W., 17 lks.
A Fir, 24" dia., N.32°30'E., 40 lks.

BLM resurvey by Lynn M. Roseberry and Rollin D. Aanrud, Cadastral Surveyors, Under Group #865, surveyed July/Oct. 1975 (DCSO Records Vol. 42 Page(s) 16528-29)

Former standard cor. of secs. 34 & 35, changed to an angle point by Chapman and Nicklin, determined at record distance from the original bearing trees:

A Fir, 23" dia., bears N.40½°E., 40 lks., with scribe marks SC R4W visible on partially opened blaze. (Rec. N.32°30'E.)

A Fir, 17" dia., bears N.44½°W., 17 lks., with scribe marks visible on partially opened blaze. (Rec. N.40°W.)

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:

AP 2
T32S R4W
S 35
1975