

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 540100

PRIMARY CORNER DESCRIPTION South 1/4 Cor. Secs. 35 only.

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

NOT IN DOUGLAS COUNTY

BLM resurvey by Lynn M. Roseberry and Rollin D. Aanrud, Cadastral Surveyors, Under Group #865, surveyed July/Oct. 1975 (DCSO Records Vol. 42 Page(s) 16545)

-----  
The point for the  $\frac{1}{4}$  sec. cor. of secs. 35 only, T32S R4W is at midpoint on the S. bdy. of sec. 35.

Set an iron post, 28" long, 2 $\frac{1}{2}$ " dia., 24" in the ground, with brass cap mkd:

T32S R4W  
 $\frac{1}{4}$  S 35  
1975

from which

A Fir, 12" dia., bears N.89°E., 7 $\frac{1}{2}$  lks., mkd:  $\frac{1}{4}$  S35 BT.

A Sugar Pine, 22" dia., bears N.39°W., 80 lks., mkd:  $\frac{1}{4}$  S35 BT.

From this point, the former standard cor. of secs. 34 & 35, changed to an angle point by Chapman and Nicklin, bears S.89°30'W., 10.89 chs. dist.