

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 540300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 and 26

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8493)

Falls on a basalt stone 30 x 18 x 16 ins. above ground. I cut a cross at exact point for 1/4 sec. corner and mark 1/4 on N. side; from which

A Fir 30" dia., bears S.21°E., 13 lks. mkd. 1/4 S BT.

A Maple 10" dia., bears N.48°W., 32 lks. mkd. 1/4 S BT.

This corner is about 800 ft. below sec. corner.

Survey by Gerald Nygren, L.S. #1035 - Nov. 2, 1989 - C.S. File 63/51

Set a 5/8" x 30" Iron rod.

BTs - 3" dia. D.Fir bears N.80°W., 25.3 ft. scribed X BT.

8" dia. D.Fir bears N.58°W., 26.3 ft. scribed 1/4 S23 BT.

8" dia. D.Fir bears S.22°E., 16.5 ft. scribed 1/4 S26 BT.

14" dia. D.Fir bears N.26°E., 5.2 ft. scribed 1/4 S23 BT.

Bruce Shaner - For: Seneca Jones Timber Co. - July 2002 - M140-41 & C.S. File 65/44-7E

Found - 5/8"x30" iron rod, from which

3" D.Fir, now dead & down, bears N.80°W., 25.3 ft.

14" D.Fir, face overgrown, bears N.58°W., 22.7 ft.
(rec. 26.3 ft.)

12" D.Fir, face overgrown, bears S.22°E., 16.5 ft.

18" D.Fir, face overgrown, bears N.26°E., 5.2 ft.

New - 6 ft. steel fence post bears West, 1.0 ft.

Note - Corner lays on old cat road, runs West from corner.