

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 11 and 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8497)

Set a basalt stone 12 x 8 x 8 ins., 8" in the ground for 1/4 sec. corner, marked 1/4 on N. face; from which
A Fir 30" dia., bears N.7 1/2°E., 49 lks. mkd. 1/4 S BT.
A Fir 48" dia., bears S.57°E., 21 lks. mkd. 1/4 S BT.
This corner is on the SW slope of spur, 100 ft. below top.

Survey by Richard L. Templin, Jr. - For: So. Oregon Plywood - May 10, 1956 - C.S. File 42/159

CORNER REPORT ONLY

The 1/4 sec. cor., which is a rock, 12 x 8 x 8 inches mkd. 1/4 on North face, from which the following original witness trees bears:

- 38" D.Fir bears N.7 1/2°E., 32.4 ft.
- 56" D.Fir bears S.57°E., 13.9 ft.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 2/18/2009 - C.S. File 67/28-18

Found - Orig. stone not found.
30" now 38" dia., 4 ft. high D.Fir stump with a fully healed single blaze, bears N.7 1/2°E., 32.4 ft. (agrees with rec.) OBT
48" now 56" dia., 5 ft. high rotted D.Fir stump scribing found "1/4 S BT" bears S.57°E., 13.9 ft. (agrees with rec) OBT
New - 2 1/2" brass cap on a 1 1/2"x32" long iron pipe is set at a position determined from OBTs, protrudes 8" out of ground. DOUGLAS COUNTY SURVEYOR

T32S R
1/4 S 11 4
S 14 W
2009

15" dia., D.Fir double blazed & scribed "1/4 S14 CS BT" bears S.88°E., 5.5 ft.

11" dia., madrone double blazed & scribed "1/4 S11 CS BT" bears N.15°E., 24.0 ft.

Note - Corner lies on steep west slope on an E-W cut line newer clear cut south of line.
Compass decl. 16 1/2°E.