

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 2 and 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8500)

Set a Madrona, 3 ft. long, 4" sq., 24" in the ground for ¼ sec. corner mkd. ¼ S on N. face, from which
A Cedar 24" dia., bears N.20°W., 31 lks. mkd. ¼ S BT.
A Madrona 10" dia., bears S.83°E., 81 lks. mkd. ¼ S BT.

Survey by G. Robert Lecklider - July 30, 1959 - M 15-31

Found - 56" I.Cedar N.20°W., 31 lks.
Set - 16" Fir N.75°E., 16.1 ft.
13" Fir N.46°W., 11.0 ft.

Douglas Co. Surveyors Office - John M. Powell, J. Heritage, W. Penley, crew - Jan. 29, 1971 - C.S. File 54/114-45

Found - Orig. 24" now 56" Cedar N.20°W., 20.5 ft., tree opened, scribe visible "S"
No trace of original Laurel BT.
16" D.Fir N.75°E., 19.8 ft. (Rec. 16.1 ft.) shows good scars. (Lecklider BT)
Set Brass cap at ¼ cor. mkd: County Surveyors Office
T 32 S R 4 W
¼ $\frac{S}{S}$ $\frac{2}{11}$
1971

Bearing trees OK, tagged same.

Ray Wytcherly - For: Swanson Group, INC. - 2/2004 - M143-78

Found - 1971 county brass cap
Orig. BT, a cedar snag stump w/county BT sign bears N.20°W., 20.5 ft.
A Fir 26" dia., bears N.75°E., 19.9 ft. to nail (16.1 M15-31) face healed over.
A Fir 21" dia., bears N.30°W., 9.2 ft. to nail (N.46°W., 11.0 ft. M15-30) face healed over.
New BT - A Cedar 10" dia., bears S.44°W., 18.8 ft. to nail scribed "S 11 ¼ BT"