

TOWNSHIP 32 RANGE 06 POINT IDENTIFIER # 576600

PRIMARY CORNER DESCRIPTION C C secs. 11 & 12, on S. bdy Sec. 2

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8502-03)

Set a Fir post 3 ft. long, 4" sq., 24" in the ground for a closing corner of secs. 11 and 12, marked C. C. T32S R4W on S.; S12 on E.; and S11 on W.; with 1 groove on E. and 5 grooves on S. faces; from which

A Fir 6" dia., bears S.9°E., 12 lks. dist., mkd. T32S R4W S12 BT.

A Fir 24" dia., bears S.55°W., 75 lks. dist., mkd. T32S R4W S11 BT.

This corner is on NW. slope of spur, 350 ft. below top.

George J. Wenderoth - August 31, 1955 - C.S. File 47/8

Found - Stump, 24" Fir S.58°W., 49.5 ft., scribe showing.
Set 1" Iron pipe for corner.

No trees available in sec. 12 and deadfall hides trees in sec. 11 - So mark trees in Sec. 2:

A 26" Fir N.40°49'W., 49.0 ft.

A 26" Fir N.41°55'E., 58.8 ft.

Corner is in bottom of gulch.

Douglas County Surveyors Office - James W. Byron - For: Doug.Co. Road Dept. - Dec. 1956/Feb. 1957 - Road drawer 48, Envelope Rd. #36

Found - 1" I.P. at corner.

NW BT as scribed by Wenderoth checks for bearing and distance, good condition.

NE BT, down.

Set Brass cap at corner alongside I.P. mkd: County Surveyors Office

S 2

Clos.Cor. S11|S12

1957

New BT - 6" Hemlock bears S.19°W., 29.1 ft. scribed S11 T32S R4W CS BT.

(Sketch in C.S. File)

GLO remonumentation by Hans W. Thielsen, under Group #'s 350 & 422, Surveyed, May/June 1959 - (DCSO records Vol. 30 Page(s) 12793-94)

The closing cor. of secs.11 and 12, on the S. bdy. of sec. 2, monumented with an iron post 1" dia., extending 10" above ground with 1957 DCSO brass cap. (Cont. Next Page)

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 576600

PRIMARY CORNER DESCRIPTION C.C. for Secs. 11 & 12, on N. bdy. S. 2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the remaining original bearing tree:
A Fir snag 26" dia., bears S.55°W., 75 lks. dist., mkd.
T32S R4W on opened blaze.
and bearing trees marked in 1957
A Hemlock 6" dia., bears S.19½°W., 49 lks. dist., mkd.
T32S R4W S12 CC CS BT.
A Fir 26" dia., bears N.42°W., 76 lks. dist., mkd. T32S
R4W S11 CC CS BT.
Stamp BLM on brass cap.

Fd. Ok by K. DeGroot, 5/2008 - M155-59
Fd. Ok by Les Fanning, 7/2008 - C.S. 65/64-8
Fd. Ok by K. DeGroot, 8/2010 - M161-16
Lat: 42°48'46.89172"N. Long: 123°07'53.71385"W.