

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 35 & 36

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

NOT IN DOUGLAS COUNTY

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8481)

-----  
Set a basalt stone, 12x8x8", 8" in the ground for ¼ sec. corner, mkd: ¼ on W. face; from which:  
A Cedar, 20" dia., bears N.75°E., 99 lks., mkd: ¼ S BT.  
A Pine, 30" dia., bears S.75°W., 17 lks., mkd: ¼ S BT.

GLO remonumentation by Hans W. Thielsen, under Group #'s 350 & 422, Surveyed, May/June 1959 - (DCSO records Vol. 30 Page(s) 12790)

-----  
The ¼ sec. cor. of secs. 35 & 36, monumented with a basalt stone, 12x8x8" firmly set, marked ¼ on W. face, from which the remaining original bearing trees:  
A sawed Cedar stump, 24" dia., bears N.75°E., 99 lks., no marks remaining.  
A Pine, 36" dia., bears S.75°W., 17 lks., with visible scribe marks.  
and a bearing tree marked by Registered Surveyor 33:  
A Pine, 12" dia., bears N.46°E., 85 lks., marked ¼ S36 RS 33 BT.

At the corner point  
Set an iron post, 28" long, 2½" dia., in the ground, with brass cap marked:

¼  
S 35 | S 36  
T32S R4W  
1959

Deposit basalt stone alongside iron post.

Fd. & used. BLM resurvey by Lynn M. Roseberry and Rollin d. Aanrud, Cadastral Surveyors, Under Group #865, surveyed July/Oct. 1975 (DCSO records Vol. 42 Page(s) 16541-42)

BLM Dependent resurvey by Ernest Q. Lundeen, Cadastral Surveyor, under Group No. 2916, surveyed June/Nov. 2018 - (DCSO records Vol. 59 Pages 23931-23932 & T32-4 Plat 2021-1)

-----  
The ¼ sec. cor. of secs. 35 and 36, reported by Roseberry and Aanrud in 1975, monumented with an iron post, 2½" dia., firmly set, projecting 12" above ground in a collar of stone with brass cap (properly) mkd. Continued next page

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 35 & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which bearing trees reported by Roseberry and Aanrud  
A pine, 17" dia., bears N.46°E., 56.1 ft., with illegible  
scribe marks visible on partially healed blaze.  
A pine, 41" dia., bears S.75°W., 11.2 ft., with no marks  
visible on partially healed blaze. (Original)  
NAD 1983 (2011)  
Lat: 42°44'54.21" N Long: 123°07'57.14" W