

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25, 26, 35 and 36

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8467-68)

Set a basalt stone 12 x 10 x 8 ins., 8" in the ground for cor. of secs. 25, 36, 35 and 26, marked with 5 notches on W. and 1 notch on E. edges; from which

A Cedar 24" dia., bears N.20°E., 278 lks. dist., mkd. T32S R4W S25 BT.

A Fir 12" dia., bears S.9°E., 89 lks. dist., mkd. T32S R4W S36 BT.

A Cedar 12" dia., bears S.88°W., 69 lks. dist., mkd. T32S R4W S35 BT.

A Pine 20" dia., bears N.9°W., 247 lks. dist., mkd. T32S R4W S26 BT.

This corner is on a hillside sloping SE. about 50 ft. above creek.

GLO remonumentation by Hans W. Thielsen, under Group #'s 350 & 422, Surveyed, May/June 1959 - (DCSO records Vol. 30 Page(s) 12790-91)

The sec. cor., monumented with a basalt stone 12x10x8 ins., firmly set, no marks remaining, from which the remaining original bearing trees:

A Cedar 30" dia., bears N.20°E., 278 lks. dist., mkd. T32S R4W S25 BT on open blaze.

A Cedar 18" dia., bears S.88°W., 69 lks. dist., mkd. T32S R4W S35 BT on open blaze.

A Pine 26" dia., bears N.9°W., 247 lks. dist., mkd. T32S R4W S26 BT on open blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 20" in the ground, with brass cap mkd:

T32S R4W
S 26 S 25
S 35 S 36
1959

from which new bearing trees:

A Cedar 6" dia., bears N.33°E., 24 lks. dist., mkd. T32S R4W S25 BT.

A Cedar 7" dia., bears S.54°E., 28 lks. dist., mkd. T32S R4W S36 BT.

A Fir 14" dia., bears S.43°W., 10 lks. dist., mkd. T32S R4W S35 BT.

A Fir 6" dia., bears N.50°W., 13 lks. dist., mkd. T32S R4W S26 BT.

Deposit basalt stone alongside iron post.