

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 25 and 26

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8483)

Set a basalt stone 20 x 12 x 8 ins. 15" in the ground for ¼ sec. cor., mkd. ¼ on W. face, from which
A Cedar 16" dia., bears N.54°E., 26 lks. dist., mkd. ¼ S BT.
A Cedar 10" dia., bears S.72°W., 14 lks. dist. mkd. ¼ S BT.
This cor. is on a hillside sloping N. 75 ft. below top of spur.

GLO remonumentation by Hans W. Thielsen, under Group #'s 350 & 422, Surveyed, May/June 1959 - (DCSO records Vol. 30 Page(s) 12791)

The ¼ sec. cor., monumented with a basalt stone, 20x12x8 ins., firmly set, mkd. ¼ on W. face, from which the remaining original bearing tree:
A Cedar 18" dia., bears N.54°E., 26 lks. dist., mkd. ¼ S on opened blaze.
At the corner point
Set an iron post, 28" long, 2 1/2" dia., 20" in the ground, with brass cap mkd: ¼
S 26 S 25
T32S R4W
1959
from which new bearing trees
A Fir 14" dia., bears N.76°E., 48 lks. mkd. ¼ S25 BT.
A Cedar 12" dia., bears S.1°W., 63 lks. mkd. ¼ S26 BT.
Deposit basalt stone alongside iron post.