

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 and 24

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8485)

-----  
Set a basalt stone 12 x 12 x 8 ins., 8" in the ground for ¼ sec. corner, mkd. ¼ on W. face, from which  
A Fir 12" dia., bears N.79°E., 150 lks. mkd. ¼ S BT.  
A Fir 12" dia., bears S.88°W., 41 lks. mkd. ¼ S BT.  
This cor. is on the SW. slope of spur, 100 ft. above creek.

GLO resurvey by Hans W. Thielsen, under Group #'s 350 & 422, Surveyed, May/June 1959 - (DCSO records Vol. 30 Page(s) 12775)

-----  
The ¼ sec. cor., monumented with a basalt stone 12x12x8 ins. firmly set, mkd. ¼ on W. face, from which the remaining original bearing tree:

A Fir snag 14" dia., bears N.79°E., 150 lks. dist., mkd. ¼ S on open blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 10" in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd: ¼

S 23 S 24

T32S R4W

1959

from which new bearing trees

A Fir 18" dia., bears N.62°E., 282 lks. mkd. ¼ S24 BT.

A Fir 12" dia., bears N.85°W., 134 lks. mkd. ¼ S23 BT.

Deposit basalt stone alongside iron post.