

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13, 14, 23 and 24

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8486)

Set a basalt stone 14 x 10 x 10 ins., 9" in the ground, for corner of secs. 13, 24, 23 and 14, marked with 1 notch on E. and 3 notches on S. edges, from which
A Cedar 24" dia. bears N.26°E., 49 lks mkd T32S R4W S13 BT
A Cedar 20" dia. bears S.26°E., 25 lks mkd T32S R4W S24 BT
A Cedar 20" dia. bears S.52°W., 18 lks mkd T32S R4W S23 BT
A Cedar 14" dia. bears N.3°W., 21 lks. mkd T32S R4W S14 BT

GLO resurvey by Hans W. Thielsen, under Group #'s 350 & 422, Surveyed, May/June 1959 - (DCSO records Vol. 30 Page 12776)

The Sec. cor., monumented with a basalt stone, 14x10x10 ins., firmly set, mkd. with 1 notch on E. and 3 notches on S. edge, from which the original bearing trees:
A Cedar 30" dia., bears N.26°E., 49 lks. mkd. with a healed blaze.
A Cedar 30" dia., bears S.26°E., 25 lks. dist. mkd. with a healed blaze.
A Cedar 30" dia., bears S.52°W., 18 lks. dist., mkd. with a healed blaze.
A Cedar 20" dia., bears N.3°W., 21 lks. dist., mkd. T32S R4W S14 on open blaze.

At the corner point
Set an iron post, 28" long, 2 1/2" dia., 20" in the ground, with brass cap mkd:
T32S R4W
S 14 | S 13
S 23 | S 24
1959

Deposit basalt stone alongside iron post.

Douglas Co. Surveyors Office - Randall W. Smith, Deputy - Stephen J. Flause - 2/19/2009 - C.S. File 67/28-19

Found - 1959 BLM BC/IP in mound of stone. 1959
NE BT now solid stump
NW BT now solid stump
SE alive
SW BT alive.
All OBTs have good dist. from BC bearings have a 4° rotation with our compass left.
Compass decl. 16½°E.