

PRIMARY CORNER DESCRIPTION Sec. Cor. for Secs. 11, 12, 13 and 14

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO rec Vol 20 Page 8488)

Set a Fir post, 3 ft. long, 4" sq., 24" in the ground for cor. of secs. 11, 12, 13 and 14, marked T32S S12 on NE.; R4W S13 on SE.; S14 on SW.; and S11 on NW. faces, with 1 notch on the E. and 4 notches on S. edges; from which

- A Fir 20" dia., bears N.7°E., 66 lks. mkd. T32S R4W S12 BT
- A Fir 18" dia., bears S.46°E., 64 lks. mkd. T32S R4W S13 BT
- A Fir 24" dia. bears S.40°W., 144 lks mkd. T32S R4W S14 BT
- A Fir 20" dia. bears N.70°W., 102 lks mkd. T32S R4W S11 BT

Survey by Richard L. Templin, Jr. - For: So. Oregon Plywood Corp. - April/May 1956 - C.S. File 42/159

Monument with a basalt stone 10x7x7", 5" in ground from which
32" D.Fir snag bears N.7°E., 43.6 ft. blaze evident.
24" D.Fir bears S.46°E., 42.3 ft. scribing visible.
40" D.Fir snag bears S.40°W., 95.1 ft. blaze evident.
28" D.Fir bears N.70°W., 67.6 ft. blaze healed.

Scribe the following new witness trees:

- 6" D.Fir bears N.40°30'E., 20.3 ft. mkd. S12 BT RE3024
- 12" D.Fir bears S.25°55'W., 62.0 ft. mkd. S14 BT RE3024

GLO remonumentation by Hans W. Thielsen, under Group #'s 350 & 422, Surveyed, May/June 1959 - (DCSO rec Vol 30 Page 12792)

The Sec. cor., determined at record bearing and distance from each of the original bearing trees:

- A Fir snag 24" dia., bears N.7°E., 66 lks. mkd. S12 on opened blaze.
- A Fir 28" dia bears S.46°E., 64 lks mkd R4 on opened blaze
- A Fir snag 36" dia., bears S.40°W., 144 lks. mkd. B on opened blaze.
- A Fir 38" dia bears N.70°W. 102 lks. mkd with healed blaze

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 20" in the ground, with brass cap mkd:

T32S R4W
S11|S12
S14|S13
1959

from which new bearing trees

- A Fir 8" dia., bears N.39°E., 29 lks. mkd. T32S R4W S12 BT
- A Fir 12" dia., bears S.27½°W., 95 lks. T32S R4W S14 BT.

Fd. Ok by Les Fanning, 7/2008 - C.S. 65/64-8

Fd. Ok by K. DeGroot, 8/2010 - M161-16

Lat: 42°47'57.02946"N Long: 123°07'54.72221"W.