

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 11 & 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8501-2)

Set a white quartz stone 20x14x8", 15" in the ground for ¼ sec. cor. mkd. ¼ on W face, from which

 A dead fir, 16" dia., bears S.77°E., 38 lks., mkd: ¼ S BT.

 A dead fir, 36" dia., bears S.36°W., 23 lks., mkd: ¼ S BT.

This corner is o a steep S. slope, 50 ft. above ravine.

Les Fanning - Silver Butte Timber Co. - 7/2008 - C.S. 65/64-8

Found - White quartz stone 10"x14"x8" lying on surface of the ground & out of position, with no visible markings.

 Orig. BT 36" rotted fir stump bears S.36°W., 15.2 ft. with axe marks visible on bark.

Set - 1¼"x28" iron pipe, 22" in the ground, with a 2½" brass cap stamped: T32S R4W

 I buried White ¼
 quartz stone S 11|S 12
 on south side 2008
 of monument PLS 2664

New BTs- 6" D.Fir bears S.57½°E., 18.3 ft. scribed "¼ S12 BT"
 17" D.Fir bears S.60¼°W., 21.6 ft scribed "¼ S11 BT"

New RMs- 5/8"x30" I.R. with 1½" alum. cap mkd: "BTS ENG-SURV
 BO-1 PLS 2664" bears N.61°57'33"E., 20.79 ft.
 5/8"x30" I.R. with 1½" alum. cap mkd: "BTS ENG-SURV
 BO-2 PLS 2664" bears N.14°58'39"W., 26.18 ft.

All New BTs have double blazed faces with a brass washer stamped "PLS 2664" nailed into the lower blaze. Bearings are taken to the center of the tree at the root crown & distances are measured to a nail in the root crown at the side & center of the tree with a total station. All BTs have a 6" Red band painted around the tree & the blazed face painted red & BT signs nailed to the tree.

Fd. Ok by K. DeGroot, 8/2010 - M161-16
 Lat: 42°48'23.65595"N. Long: 123°07'54.08505"W.