

PRIMARY CORNER DESCRIPTION Sec. cor. 1 & 2 only, on N. bdy Sec. 12

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 20 Page(s) 8456)

Set post corner to secs. 1, 2, 11 and 12, from which
A Fir 6" dia., bears N.22°E., 8 lks. dist.
A Fir 5" dia., bears S.80°E., 8 lks. dist.
A Fir 12" dia., bears S.62°W., 42 lks. dist.
A Chinquapin 10" dia., bears N.53°W., 15 lks. dist.

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8502)

The Sec. cor., 1, 2, 11 and 12, which I find in a delapidated condition; and which I reestablish from the bearing tree in sec. 11, the only one standing, as follows:
Set a Fir post, 3 ft. long, 4" sq., 24" in the ground, for a corner of secs. 1 and 2, marked T32S S1 on NE.; and R4W S2 on NW. faces; with 1 notch on E. edge; from which
A Fir 6" dia., bears N.27°E., 23 lks. dist., mkd. T32S R4W S1 BT.
A Fir 14" dia., bears N.63°W., 70 lks. dist., mkd. T32S R4W S2 BT.

Douglas Co. Surveyors Office - James W. Byron - For: Douglas Co. Road Dept. - Dec. 1956/Feb. 1957 - Road drawer #48 Envelope Rd. #36

Found - Orig. 6" Fir now 12" N.27°E., I do not open, shows old blaze.
Orig. 14" Fir, face open, scribing visible. BTs check.
Set Brass cap at corner marked Closing Corner S2|S1 T32S R4W
S 12
County Surveyors Office
Scribe - 12" Fir N.70°E., 24.5 ft. S1 T32S R4W CS BT.

GLO remonumentation by Hans W. Thielsen, under Group #'s 350 & 422, Surveyed, May/June 1959 - (DCSO records Vol. 30 Page(s) 12793)

The cor. of secs. 1 and 2 on the N. bdy. of sec. 12, remonumented with an iron post, 1" dia., extending 13" above ground, with brass cap mkd. County Surveyors Office T32S R4W closing cor. secs. 1 and 2 1957, from which bearing trees mkd. by Nicklin in 1897:
(Cont. Next Page)

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 600600

PRIMARY CORNER DESCRIPTION Sec. cor. 1 & 2 only, N. bdy. Sec. 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir 12" dia., bears N.27°E., 23 lks. dist., mkd. with a healed blaze.
A Fir 24" dia., bears N.63°W., 70 lks. dist., mkd. with a healed blaze.
and a bearing tree mkd. in 1957:
A Fir 12" dia., bears N.71°E., 37 lks. dist., mkd. T32S R4W S1 CS BT.
At the corner point
Set an iron post, 28 ins. long, 2 1/2 ins. dia., 20 ins. in the ground, with brass cap marked
T32S R4W
S 2 | S 1
S 12
1959
Deposit County post alongside iron post.

Fd. OK - Gerald Nygren - Nov. 1996 - M 124-34
Fd. Ok by K. DeGroot, 5/2008 - M155-59
Fd. Ok by K. DeGroot, 8/2010 - M161-16
Lat: 42°48'46.67829"N. Long: 123°07'49.69616"W.

2