

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 600700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 2; and 35 & 36, T31-4

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 18 Page(s) 7784-85)

Set post, cor. to secs. 1, 2, 35 and 36, from which
A Fir 16" dia., bears N.38°E., 48 lks. dist.
A Laurel 8" dia., bears S.20°E., 13 lks. dist.
A Fir 5" dia., bears S.22°W., 20 lks. dist.
A Laurel 10" dia., bears N.20°W., 30 lks. dist.

Cor. Fd. and used in GLO survey by Wm. Bushey, Contract #620, dated June 17, 1893 (DCSO records, Vol. 18 Page 7801)

George Wenderoth, Deputy Co. Surveyor - Dec. 1947 - C.S. File 46/134

Found 4 old BTs.
24" Fir bearing N.32°10'E., 30.3 ft.
16" Madrona bearing N.24°54'W., 20.9 ft.
14" Fir bearing S.30°50'W., 13.2 ft.
10" Madrona bearing S.5°45'E., 8.6 ft.
Drove a 1" I.Pipe for the corner.
Marked:
A 14" Fir bearing S.14°30'W., 20.5 ft.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, Joe Brady, crew - Feb/ 1966 - C.S. File 54/20-32

Found - Iron pipe at corner.
Orig. 24" Fir N.32°10'E., 30.3 ft., shows good scar.
Orig. 16" now 19" Laurel N.24°54'W., 20.9 ft., scribe visible.
Orig. 14" now 17" Fir S.30°50'W., 13.2 ft., open, no scribing.
Orig. 10" Laurel S.5°45'E., 8.6 ft., very rotten.
14" Fir down, S.25°E., 22.7 ft.

Set Brass cap at cor. mkd: County Surveyors Office
T31S S 35 | S 36
T32S S 2 | S 1 R4W
1966

B.C. set alongside I.P.
Rescribe-19" Laurel N.24°54'W., 20.9 ft. "T31S R4W S2 CS BT"
New BTs -8" Fir S.46°W., 18.7 ft. scribed "T32S R4W S2 CS BT"
8" Laurel S.27°E., 29.9 ft. scribed "T32S R4W S1 CS BT"

Fd. OK - Gerald Nygren - Nov. 1996 - M 124-34

