TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 640300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 24 and 25

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8484)

Set a basalt stone 16 x 14 x 8 ins., 10" in the ground for ¼ sec. corner, mkd. ¼ on N. face, from which
A Fir 10" dia., bears S.42°E., 35 lks. mkd. ¼ S BT.
A Fir 12" dia., bears N.75°W., 41 lks. mkd. ¼ S BT.
This corner is on the top of a ridge, bearing N. and S., 600 ft. above sec. cor.

GLO Subdivision of sec. by Hans W. Thielsen, under Group #'s 350 & 422, Surveyed, May/June 1959 - (DCSO records Vol. 30 Page(s) 12783)

The ¼ sec. cor., monumented with a basalt stone 16x14x10 ins., firmly set, mkd. ¼ on N. face.
At the corner point
Set an iron post, 28" long, 2 1/2" dia., 10" in the ground, to solid rock and in a mound of stone, 3 ft. base, to top, with brass cap mkd:

¼ S 24 / S 25
T32S R4W
1959

from which
A Fir 7" dia., bears N.12¼°E., 12 lks. mkd. ¼ S24 BT.
A Fir 6" dia., bears S.32¼°E., 21 lks. mkd. ¼ S25 BT.
Deposit basalt stone alongside iron post.