TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8486-87)

---

Set a basalt stone 12 x 10 x 6 ins., 8" in the ground for ¼ sec. corner, marked ¼ on N. face, from which
A Fir 24" dia., bears S.80°W., 31 lks. mkd. ¼ S BT.
A Chinquapin 8" dia., bears N.55°W., 52 lks. mkd. ¼ S BT.
This cor. is on the top of spur, sloping N.20°E., 350 ft. above sec. cor.

GLO Sec. Subdivision by Hans W. Thielsen, under Group #'s 350 & 422, Surveyed, May/June 1959 - (DCSO records Vol. 30 Page(s) 12784)

---

The ¼ sec. cor., monumented with a basalt stone, 12x10x6 ins., firmly set, mkd. ¼ on N. face, from which the remaining original bearing tree:
A Fir snag 30" dia., bears S.80°W., 31 lks. mkd. with a healed blaze.
At the corner point
Set an iron post, 28" long, 2 1/2" dia., 20" in the ground, with brass cap mkd:

¼ S 13
S 24
T32S R4W
1959

from which new bearing tree
A Chinquapin 6" dia., bears N.63°W., 24 lks. mkd. ¼ S13 BT
A Chinquapin 6" dia., bears S.7½°E., 43 lks. mkd. ¼ S24 BT
Deposit basalt stone alongside iron post.