

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 & 36 East line, only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO rec Vol. 20 Pg 8380)

Set a basalt stone 16x12x10 ins., 10" in the ground, for cor. of secs. 30, 31, 36 and 25, marked with 5 notches on N. and 1 notch on S. edges, from which

A Fir 24" dia., bears N.40°E., 79 lks mkd. T32S R3W S30 BT

A Fir 24" dia., bears S.60°E., 22 lks mkd. T32S R3W S31 BT

A Fir 24" dia. bears S.75°W., 33 lks. mkd. T32S R4W S36 BT

A Pine 12" dia., bears N.1°W., 104 lks mkd T32S R4W S25 BT

This cor. is on a hillside, sloping South about 500 ft. below top of ridge.

GL0 survey by Fred Mensch under special Instructions dated August 20, 1912 (DCSO records Vol. 20 Page(s) 8393)

The Sec. cor., which is a stone, firmly set, marked and witnessed as described by the Surveyor General and which I now change to refer to Secs. 25 and 36 only, and destroy the marks on the old bearing trees in Secs. 30 and 31.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, W. Penley & V. Tracy, crew - Aug. 1969 - C.S. File 54/91-58

Found - No trace of corner stone.
Orig. 24" now 28" D.Fir, S.75°W., 21.8 ft., shows good scribing and good BT face.
12" now 16" S.Pine N.1°W., 68.6 ft. shows good scribing.

Set Brass cap at cor. mkd: County Surveyors Office

R	T 32 S	R
4	S 25 S 30	3
W	S 36	W
	1969	

No new BTs needed. Corner lies about 100 ft. N. of a creek.

BLM Dependent resurvey by Ernest Q. Lundeen, Cadastral Surveyor, under Group No. 2916, surveyed June/Nov. 2018 - (DCSO records Vol. 59 Pages 23931-23932 & T32-4 Plat 2021-1)

The cor. of secs. 25 and 36 only, on the E. bdy. of the Tp., perpetuated by the Douglas County Surveyor's Office in 1969, ; monumented with an iron post, 1½" dia. firmly set, projecting 12 ins. above a mound of stone, 3 ft. base, 2 ft. high with brass cap (properly) mkd.
from which original bearing trees

continued next page

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 & 36 East line, only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 31" dia., bears S.73¼°W., 21.8 ft., with no marks visible on partially healed blaze. (Record, S.75°W.)
A pine, 22" dia., bears N.3°W., 63.3 ft., with no mark visible on partially healed blaze. (Record, N.1°W., 68.6 ft.)