

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 25 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8380)

Set a basalt stone 14x8x8 ins., 9" in the ground, for ¼ sec. cor., marked ¼ S. on West face, from which

A Cedar 20" dia., bears N.68°E., 8 lks. dist., mkd. ¼ S BT.

A Fir 18" dia., bears S.82°W., 7 lks. dist., mkd. ¼ S BT.
This cor. is on a hillside, sloping NW. about 300 ft. above creek.

GLO survey by Fred Mensch under special Instructions dated August 20, 1912 (DCSO records Vol. 20 Page(s) 8394)

Intersect the ¼ cor. of secs. 25 and 30, which is a stone, firmly set, marked and witnessed as described by the Surveyor General. I now change this cor. to refer to Sec. 25 only, and rewitness as follows: From the cor.

A Fir 18" dia., bears S.82°W., 7 lks. dist., mkd. ¼ S25 BT

A Fir 30" dia., bears N.21°W., 41 lks. dist., mkd. ¼ S25 BT.

I destroy the marks on former bearing tree referring to Sec. 30.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, W. Penley & V. Tracy, crew - August 1969 - C.S. File 54/91-56

Found - Corner stone 14x8x8, firmly set mkd. "¼" on West face.

Orig. 18" D.Fir now snag, S.82°W., 4.6 ft. opened for scribe.

Orig. 30" D.Fir now stob, N.21°W., 27.1 ft., face burnt.

Set Brass cap at cor. mkd. County Surveyors Office

R	T 32 S	R
4	¼	3
W	S 25	W
	1969	

New BTs -6" D.Fir S.6°W., 10.0 ft. mkd. ¼ S25 CS BT.

12" D.Fir N.14°W., 26.7 ft. mkd. ¼ S25 CS BT.