

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25 only, E. bdy.

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8378-79)

Set a basalt stone 14x8x8 ins., 9" in the ground for cor. of secs. 19, 30, 25 and 24, marked with 4 notches on North and 2 notches on South edges, from which

- A Fir 18" dia., bears N.58°E., 87 lks. dist., mkd. T32S R3W S19 BT.
- A Fir 36" dia., bears S.80°E., 61 lks. dist., mkd. T32S R3W S30 BT.
- A Cedar 24" dia., bears S.62°W., 34 lks. dist., mkd. T32S R4W S25 BT.
- A Pine 48" dia., bears N.62°W., 70 lks. dist., mkd. T32S R4W S24 BT.

This cor. is on a hillside, sloping East.

GLO survey by Fred Mensch under special Instructions dated August 20, 1912 (DCSO records Vol. 20 Page(s) 8395)

Intersect the cor. of secs. 19, 24, 25 and 30, which is a stone, firmly set, marked and witnessed as described by the Surveyor General. I now change this cor. to refer to Secs. 24 and 25 only and destroy the marks on the old bearing trees in Secs. 19 and 30.

GLO remonumentation by Hans W. Thielsen, under Group #'s 350 & 422, Surveyed, May/June 1959 - (DCSO records Vol. 30 Page(s) 12786)

The Sec. cor., monumented by Nicklin in 1897, with a basalt stone, firmly set, 14x8x8 ins., no marks remaining, from which the original 1897 bearing trees:

- A Fir 24" dia., bears N.58°E., 87 lks. dist., mkd. with a healed blaze.
- A Fir snag 48" dia., bears S.80°E., 61 lks. dist., mkd. with an opened blaze.
- A fallen Cedar 30" dia., bears S.62°W., 34 lks. dist., mkd. with a healed blaze.
- A Pine snag 50" dia., bears N.62°W., 70 lks. dist., mkd. S24 on open blaze.

At the corner point
 Set an iron post, 28 ins. long, 2 1/2 ins. dia., 20 ins. in the ground, with brass cap marked

T32S	T32S
<u>S 24</u>	S 19
S 25	
R4W	R3W
1959	

(Cont. Next Page)

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 700300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25 only, E. bdy

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

from which new bearing trees
A Fir 5" dia., bears N.50°W., 20 lks. dist., mkd. T32S R4W
S24 BT.
A Cedar 30" dia., bears S.48°W., 77 lks. dist., mkd. T32S
R4W S25 BT.
Deposit basalt stone alongside iron post.