

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13 & 24 only, E. bdy.

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8377)

Set a basalt stone 14x12x6 ins., 9" in the ground, for cor. of secs. 18, 19, 24 and 13, marked with 3 notches on N. and S. edges, from which

- A Chinquapin 7" dia., bears N.88°E., 24 lks. dist., mkd. T32S R3W S18 BT.
- A Madrona 8" dia., bears S.39°E., 19 lks. dist., mkd. T32S R3W S19 BT.
- A Cedar 50" dia., bears S.40°W., 11 lks. dist., mkd. T32S R4W S24 BT.
- A Fir 24" dia., bears N.57°W., 23 lks. dist., mkd. T32S R4W S13 BT.

This cor. is on hillside sloping South 25 ft. below top of last spur.

GLO survey by Fred Mensch under special Instructions dated August 20, 1912 (DCSO records Vol. 20 Page(s) 8396)

Intersect the cor. of secs. 13, 18, 19 and 24, which is a stone, firmly set, marked and witnessed as described by the Surveyor General, except that the old bearing trees in Secs. 18 and 19 have been destroyed by fire. I now change this cor. to refer to Secs. 13 and 24 only.

GLO resurvey by Hans W. Thielsen, under Group #'s 350 & 422, Surveyed, May/June 1959 - (DCSO records Vol. 30 Page(s) 12774-75)

The cor. of secs. 13 and 24 only, monumented by Nicklin with a basalt stone 14x13x6 ins., firmly set, marked with 3 grooves on N. and S. faces, from which the remaining original bearing trees:

- A Cedar 47" dia., bears S.40°W., 11 lks. dist., mkd. T32S R4W S24 on opened blaze.
- A Fir 37" dia., bears N.57°W., 23 lks. dist., mkd. with a healed blaze.

At the corner point
Set an iron post, 28 ins. long, 2 1/2 ins. dia., 20 ins. in the ground, with brass cap marked

T32S
R4W R3W
S 13 S 18
S 24
1959

from which a new bearing tree
(Cont. Next Page)

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 700400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 13 & 24 only, E. bdy.

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir 13" dia., bears S.23½°W., 80 lks. dist., mkd. T32S
R4W S24 BT.
Deposit basalt stone alongside iron post.