

PRIMARY CORNER DESCRIPTION Sec. Cor. for 12 & 13; 7 & 18, T32-3

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 20 Page(s) 8360)

-----  
Set post. cor. to Secs. 7, 12, 18 and 13, from which  
A Fir 12" dia., bears N.32°E., 76 lks. dist.  
A Laurel 10" dia., bears S.70°E., 21 lks. dist.  
A Laurel 29" dia., bears S.50°W., 20 lks. dist.  
A Fir 36" dia., bears N.28°W., 31 lks. dist.

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8375-76)

-----  
The established cor. of secs. 7, 12, 13 and 18, which I find in a dilapidated condition, and which I reestablished at the same point as follows:

Set a Cedar post 3 ft. long, 4" sq., 24" in the ground, mkd. T32S S7 on NE.; R3W S18 on SE.; S13 on SW.; and R4W S12 on NW. faces; with 2 notches on N. and 4 notches on S. edges, from which

- A Fir 12" dia., bears N.32°E., 76 lks. mkd. T32S R3W S7 BT
- A Fir 24" dia., bears S.72°E., 56 lks. mkd. T32S R3W S18 BT.
- A Laurel 20" dia., bears S.50°W., 20 lks. mkd. T32S R4W S13 BT.
- A Fir 36" dia., bears N.28°W., 31 lks. mkd. T32S R4W S12 BT.

GLO remonumentation by Hans W. Thielsen, under Group #'s 350 & 422, Surveyed, May/June 1959 - (DCSO records Vol. 30 Page(s) 12786-87)

-----  
The Sec. cor., determined at record bearing and distance from each of the remaining bearing trees mkd. by Byars in 1871:

- A Fir 25" dia., bears N.32°E., 76 lks. dist., mkd. with a healed blaze.
- A fallen Fir 38" dia., bears N.28°W., 31 lks. dist., no marks remaining.

and bearing trees marked in 1897 by Nicklin:

- A Fir 36" dia., bears S.73°E., 52 lks. dist., mkd. with a healed blaze. (Rec. bears S.72°E., 56 lks. dist.)

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 20 ins. in the ground, with brass cap marked

(Cont. Next Page)

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 700500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 12 & 13; 7 & 18, T32-3

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

T32S  
R4W|R3W  
S 12|S 7  
S 13|S 18  
1959

from which new bearing trees

A Fir 55" dia., bears S.77°W., 50 lks. dist., mkd. T32S R4W S13 BT.

A Hemlock 10" dia., bears N.50°W., 62 lks. dist., mkd. T32S R4W S12 BT.

Kris DeGroot - For Silver Butte Timber Co. - 8/2010 - M161-16

-----  
Lat: 42°47'56.09244"N. Long: 123°06'41.38102"W.

Found - USBLM BCIP by Hans W. Thielsen, Cadastral Surveyor, in 1959 per USBLM Field note Volume OR-R0571, page 75 firmly set, projecting 10" above the ground, properly marked:

from which the original BTs by Byars in 1871:

A 24" buckskin fir staub bears N.33°45'E., 49.4 ft (rec. N.32°E., 76 lks) with healed low blaze

The rotted remains of a 38" fir bears N.28°W., 21.1 ft (rec. 31 lks)

And a BT by Nicklin in 1896:

A 36" rotted fir stump bears S.72°30'E., 34.5 ft. (Rec. S.73°E., 52 lks) with healed blaze

and BT by Thielsen in 1959:

A 55" Fir stump bears S.77°W. 33.9 ft to center (rec. 50 lks.)

A 24" Hemlock stump bears N.51°15'W., 41.5 ft (rec. N.50°W., 62 lks.)

New BTs- A 12" D.Fir bears N.47°45'E., 31.7 ft scribed "T32S R3W S7 BT"

A 13" D.Fir bears S.64°15'E., 26.6 ft scribed "T32S R3W S18 BT"

A 12" D.Fir bears S.83°30'W., 25.1 ft scribed "T32S R4W S13 BT"

A 11" D.Fir bears N.18°15'W., 16.7 ft scribed "T32S R4W S12 BT"