

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 12; 6 & 7 of T32-3

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W.H. Byars, Deputy Surveyor under contract # 152 survey dated June 3, 1871 (DCSO records Vol. 20 Page(s) 8359)

- 
- Set post, cor. to Secs. 1, 6, 7 and 12, from which
- A Fir 30" dia., bears N.22°E., 20 lks. dist.
  - A Chinquapin 6" dia., bears S.10°E., 37 lks. dist.
  - A Fir 8" dia., bears S.50°W., 35 lks. dist.
  - A Chinquapin 5" dia., bears N.65°W., 41 lks. dist.

GLO survey by Carl S. Nicklin, Deputy Surveyor, under Contract #664, dated May 23, 1896 (DCSO records Vol. 20 Page(s) 8498-99)

- 
- The Sec. cor., which I reestablished from the bearing tree in sec. 6; the corner and all other bearing trees had been destroyed by fire.
- Set a Fir post, 3 ft. long, 4' sq., 24" in the ground for cor. of secs. 6, 7, 12 and 1, marked T32S S6 on NE.; R3W S7 on SE.; S12 on SW.; and R4W S1 on NW. faces; with 1 notch on N. and 5 notches on S. edges, from which
- A Fir 30" dia., bears N.22°E., 20 lks. dist. mkd. T32S R3W S6 BT.
  - A Fir 24" dia., bears S.8°E., 214 lks. dist., mkd. T32S R3W S7 BT.
  - A Fir 36" dia., bears S.8½°W., 166 lks. dist., mkd. T32S R4W S12 BT.
  - A Fir 20" dia., bears N.18°W., 108 lks. dist., mkd. T32S R4W S1 BT.

George J. Wenderoth, Deputy Co. Surveyor - For: H.D. Hauck - May 1955 - C.S. File 46/134

- 
- 1" Iron pipe.
- 38" Fir N.22°E., 13.2 ft.
  - 30" Fir S.8°E., 141.2 ft.
  - 42" Fir S.8°30'W., 109.5 ft.
  - 36" Fir N.18°W., 71.3 ft.

GLO remonumentation by Hans W. Thielsen, under Group #'s 350 & 422, Surveyed, May/June 1959 - (DCSO records Vol. 30 Page(s) 12787)

- 
- The Sec. cor., determined at record bearing and distance from each of the bearing trees mkd. in 1897 by Nicklin:
- A Fir 36" dia., bears S.8°E., 214 lks. mkd. S7 on opened blaze. (Cont. Next Page)

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 700600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 12; 6 & 7 of T32-3

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

A Fir 45" dia., bears S.8½°W., 166 lks. dist., mkd. R4W on  
opened blaze.

A Fir 38" dia., bears N.18°W., 108 lks. dist., mkd. BT on  
opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. dia., 20 ins. in  
the ground, with brass cap marked

T32S  
R4W|R3W  
S 1|S 6  
S 12|S 7  
1959

from which a new bearing tree

A Fir 10" dia., bears N.36°E., 44 lks. dist., mkd. T32S  
R3W S6 BT.

Fd. OK - Gerald Nygren - Nov. 1996 - M 124-34

Fd. Ok by K. DeGroot, 5/2008 - M155-59

Fd. Ok by K. DeGroot, 8/2010 - M161-16

Lat: 42°48'47.00769"N. Long: 123°06'40.48485"W.