

TOWNSHIP 32 RANGE 04 POINT IDENTIFIER # 988020

PRIMARY CORNER DESCRIPTION Cor. #3, M.S. #148

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Surveyed by W.F. Briggs, U.S. Deputy Mineral Surveyor - For:
Green Mountain Mining Company - May 9, 1887 - (DCSO records
Vol. 28 Page(s) 11824)

Set post No. 3; from which
A Fir 20" dia., bears S.22°W., 28 lks. dist.
A Fir 12" dia., bears N.64°E., 31 lks. dist.

Survey by Terrence Nickerson - For: Bureau of Land Management
- Preliminary survey, Medford District - Aug. 17, 1979 - C.S.
File 58/206 and M 78-42

Found - A sawed Fir stump 24" dia., bears S.67 3/4°E., 20.5
ft. with scribe marks BT visible on opened face.
(Rec. N.64°E., 31 lks.) The face of the blaze
fits the S.67 3/4°E. bearing, it is my assumption
that Briggs erred when he recorded the bearing
to this tree.

A sawed Fir stump, 36" dia., bears S.20¼°W., 18.5
ft., no blaze visible, the stump has been cut too
low to leave the blaze. (Rec. S.22°W., 28 lks.)

Set an iron rod, 5/8" dia., 20" in the ground.
New BT - 25" Fir bears N.89°E., 19.1 ft.