

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 100240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 30; & 25 of T32-6

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

Original - George W. Hyde and Wells Lake, under Contract #54 dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8553)

Set qr. sec. post, from which
A Thorn, 9" dia., bears S.50°E., 20 lks.
An Ash 20" dia., bears S.76°W., 36 lks.

G.J. Wenderoth, Surveyor - Wit: F. Loso and C. Smith - April 6, 1949 - M 32-2 and C.S. File 40/268

Set halfway bet. sec. corners.
Drove 1" I.P. for corner.
Scribe - 14" Maple S.51°30'W., 399.0 ft.
7" Ash N.65°30'W., 134.8 ft.

Douglas Co. Surveyors Office - John Powell, Frank Jones and J. Brady, crew - Sept. 1967 - C.S. File 53/52-43

Found - 1" Iron pipe in North-South fence line. See signed statement by Chet Smith, Jr. in C.S. File 53/52.
7" Ash N.65½°W., 134.8 ft., found stob believed to be this tree.
No trace of SW bearing tree.
New BTs -9" Ash (?) South, 55.4 ft. mkd. S30 CS BT.
8" Ash N.74°E., 138.0 ft. mkd. ¼ S25 CS BT.
This corner lies in N-S fence line 220.0 ft. North of R/W fence. Location tag on R/W fence line.

Fd. OK, by Donald Bentz, Sept. 1986, M 102-39
Fd. 1" IP by Bart Heichel, 12/2022 - M181-68