

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 100700

PRIMARY CORNER DESCRIPTION Tsp. Cor; NW Cor. Sec. 6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Geo. W. Hyde, Deputy Surveyor under contract No.54 dated Feb. 19, 1855 - (DCSO rec. Vol 19, pg. 7880)

Set post cor. to Tps. 31 & 32 S. Rs. 5 & 6 W., from which:
A Maple, 12" dia. bears N.85°E., 9 lks. dist.
A Fir, 18" dia. bears S.61°E., 53 lks. dist.
A Fir, 18" dia. bears N.55°W., 16 lks. dist.
A Yew, 5" dia. bears S.75°W., 88 lks. dist.

Douglas Co. Surveyors Office - Geo. J. Wenderoth, for C.& D. Lumber Co. Feb. 1964 - C.S. File 49/92-8.

Set - 1" Iron Pipe at corner.
Scribed - 52" Fir, S.35°35'E., 13.6 ft.
 12" Hemlock, S.46°12'W., 32.2 ft.
 16" Yew, N.79°40'W., 97.4 ft.

Oregon St. Bd. of Forestry, Arnold G. Gibson - July 15, 1966 C.S. File 55/6 (See also C.S. 49/92-9 for 1964 correspondence concerning this corner - added 6/16/2021)

Original - No evidence of Orig. record corner post or BT's could be identified.
Found - Fir described in C.S. File No. 49/92 by Dep. Co. Surveyor Geo. J. Wenderoth, April 11, 1959, stating that a 52" Fir with scribes on N. face was found, near which the Township corner was set by a straight line intersection of lines N & S and E & W. The sugar pine line trees N. & S. were not used for control, nor was the S $\frac{1}{4}$ Corner of Sec. 31, which has been subsequently identified and restored. - The above 52", now 55" Fir has very old bark scribed "T32 R6W S1 BT", facing N.15°E., They are similar in size, shape & style to other Lake and Hyde work in this area. - Orig. line blazes were found on line E. of this tree. Line blazes were found S. & the distance to the ridge top matches the record. The E & W creek at 2.00 ch. N. is in place. (Approx. 60 ft. W. & on a line N. across the creek to the main ridge numerous blazes were found. None of them were exposed. They appeared very old & ended North of creek. A search at a point S. of these blazes & 2.00 ch. S. of the creek disclosed only a 40" Fir in the NW & a 16" Yew in the SW which did not match each other or the point. No scribes or axe marks were found on either tree, although both were green.)
Restored - Set 1 $\frac{1}{2}$ " x 36" gal. I.Pipe with 3" Brass Cap marked: "ORE ST BD of FORESTRY T31SR6WR5WS36 S31 S6 S1 T32S 1966 RS 359" from which

(Cont. Next Page)

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 100700

PRIMARY CORNER DESCRIPTION Tsp. Cor. ; NW Cor. Sec. 6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

55" Fir bears S.15°W., 11.5 ft. scribed "T32S R6W S1 BT"
(also scribes S6 CS BT by Wenderoth)
6" Fir bears N.86°W., 54.5 ft. scribed "T31S R6W S36 BT"
4" Hemlock bears S.58°E., 28.3 ft. scribed "x"
4" Fir bears N.9°E., 19.0 ft. scribed "x"
Wenderoth's 3/4" pipe bears West 13.3 ft.
Set 4" x 4" x 72" white painted Cedar post 2.0 ft. south of
corner pipe. Ore St. Forestry Dept. metal location poster
on 55" Fir BT. Also BLM poster on 36" Fir 150.0 ft. N. on
N. side of creek.

Douglas Co. Surveyors Office - Randall Smith, Stephen Flause;
Jan. 7, 1992 - C.S. File 64/23-2

Found - 1966 Ore. State Board of Forestry 3" Brass Cap on a
1½" O.D. iron pipe protruding 7" above ground.
1" O.D. iron pipe protrudes 5" above ground (Wenderoth)
1" I.P. bears West, 13.3 ft. from OSBF BC/IP.
55" now 58" dia. D.Fir with a fully healed single blaze on
the NW trunk and bark scribed "LS 359" on North trunk,
bears S.15°W., 13.8 ft. (Rec. S.15°W., 11.5 ft. dist.
to bark scribing)
4" now 9" dia. 1½ ft. high Hemlock stump with a fully
healed blaze, bears S.58°E., 28.3 ft.
4" now 11" dia., D.Fir with a fully healed single blaze,
bears N.9°E., 19.0 ft (agrees with rec) added 11/6/2019
6" now 12" dia. 1½ ft. high D.Fir stump with a fully
healed single blaze, bears N.86°W., 54.5 ft.
New BTs - (Going to corner position as determined by Ore. St.
Bd. of Forestry)
8" dia. Hemlock double blazed and scribed "T31S R6W S36 CS
BT" bears N.43°W., 12.1 ft.
7" dia. Hemlock double blazed and scribed "T31S R5W S31 CS
BT" bears N.75°E., 16.6 ft.
Corner lies on a steep north facing slope.
See C.S. File 49/92-9 for correspondence on the establishment
of the corner position.)

BLM dependent resurvey by Kevin G Mulder, under Group No.
2925; Surveyed July/Oct. 2018 - (DCS0 recs Vol. 59 Pg 23762)

The cor. of Tps. 31 & 32 S., Rs. 5 & 6 W., restored by Gibson
in 1966, perpetuated by the Douglas Co. Surveyor's Office in
1992, and is accepted as the best available evidence of the
position of the original cor.; monumented with an iron post,
1½" dia., firmly set, projecting 8 ins. above the ground,
with brass cap (properly) mkd.
continued next page

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 100700

PRIMARY CORNER DESCRIPTION Tsp. Cor; NW Cor. Sec. 6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the remains of bearing trees mkd. by Gibson
A fir, 19" dia., bears N.8½°E., 19.2 ft., with a healed blaze.
A broken off fir snag, 58" dia., bears S.15¼°W., 13.6 ft., with scribe marks 359 visible on bark and a healed blaze facing NW.
and BTs mkd. by the Douglas County Surveyor's Office
A hemlock, 13" dia., bears N.75¼°E., 16.8 ft., with a healed double blaze.
A hemlock, 12" dia., bears N.41¼°W., 11.9 ft., with a healed double blaze.
and new bearing trees
A hemlock, 10" dia., bears S.42¾°E., 25.4 ft., mkd. X at breast height and BT at the base.
A hemlock, 7" dia., bears S.81½°W., 18.3 ft., mkd. T32S R6W S1 BT.
From this cor., a point established by George J. Wenderoth, in 1959, bears N.89°26'53"W., 13.14 ft. No determination was made as to the method(s) utilized by Wenderoth in establishing this position and was therefore not utilized during the course of this survey; monumented with an iron pipe, 1" dia., firmly set, projecting 3" above the ground, from which a bearing tree mkd. by Wenderoth
A broken off fir snag, 58" dia., bears S.35¾°E., 16.4 ft., with a healed blaze and scribe marks 359 visible on bark facing NE. Note: This tree is the same (SW) tree subsequently bark scribed by Gibson in 1966.