

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 140200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 30 and 31

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - GLO survey by Wells Lake, Deputy Surveyor, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8576)

Set Qr. sec. post, from which
A Cedar 11" dia., bears S.62½°W., 125 lks.
A Cedar 18" dia., bears N.18°W., 166 lks.

GLO survey by Oscar F. Thiel, Deputy Surveyor, under Contract #729, dated Dec. 24, 1900 and special instructions dated Sept. 12, 1901 (DCSO records Vol. 20 Page(s) 8620)

The ¼ sec. cor. post having disappeared, I set a Cedar post, 3 ft. long, 3" sq., 24" in the ground, for ¼ sec. cor., marked ¼ S30 on N. face and 31 on S. face; and witnessed as described by the surveyor general.

George Baker - Wit: R. Asbarray and E. DeBell - April 25, 1947 - C.S. File 40/3

I found a squared stake scribed (¼S). BTs OK as per notes. I set 1" Axle in place of stake for corner.

Douglas Co. Surveyors Office - John M. Powell, Frank Jones, Joe Brady, crew - July 1967 - C.S. File 53/52-55

Found - 1" axle at corner.
11" Cedar now 20", S.62½°W., 82.5 ft., shows scribing in bark.
No trace of NW BT.
New BTs -16" D.Fir S.41°W., 9.2 ft. mkd. ¼ S30 CS BT.
12" D.Fir N.84°E., 39.0 ft. mkd. ¼ S31 CS BT.
Corner lies on top of small spur running NW.

Fd. Ok by Ray Wytcherley, April 1997 - M 127-3

BLM Dependent resurvey by Arthur R. Rambo, & Francis Simon Cadastral Surveyors under Group No. 2143, surveyed May 2006/Feb. 2007 - (DCSO records, Vol. 55 Page(s) 21683-4)

The ¼ sec. cor. of secs. 30 and 31, perpetuated by Baker, in 1947 and further perpetuated by the Douglas County Surveyor's Office, in 1967; monumented with a steel axle, 1" dia., firmly set, projecting 8" above the ground, from which an original bearing tree:
A cedar, 37" dia., bears S.62½°W., 82.5 ft., no marks visible.
and a BT mkd. by the Douglas County Surveyor's Office **cont.**

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 140200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 30 and 31

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 24" dia., bears S.39½°W., 9.2 ft., with a healed blaze.

At the corner point
Set a stainless steel post, 28" long, 2½" dia., 23" in the ground, directly over axle, with brass cap mkd.

T 32 S R 5 W
¼ S 30
 S 31
2006

from which a new bearing tree
A fir, 12" dia., bears N. 78° W., 22.1 ft., mkd. ¼ S30 BT.
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center, unless otherwise described in the corner description
Deposit a magnet in a white plastic case at the base of the stainless steel post.

Fd. BC by Bart Heichel, 12/2022 - M181-68