

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 18 and 19

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Original - GLO survey by Wells Lake, Deputy Surveyor, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8577)

-----  
Set Qr. sec. post, from which  
A Cedar 38" dia., bears N.15°W., 25 lks.  
A Cedar 18" dia., bears S.70°E., 17 lks.

GLO survey by Oscar F. Thiel, Deputy Surveyor, under Contract #729, dated Dec. 24, 1900 and special instructions dated Sept. 12, 1901 (DCSO records Vol. 20 Page(s) 8621-22)

-----  
The ¼ sec. cor. having disappeared, I set a sandstone 12x10x10 ins., 8" in the ground, marked ¼ on N. face, from which  
A Laurel 15" dia., bears N.82°E., 76 lks. mkd. ¼ S18 BT.  
A Fir 18" dia., bears S.84½°W., 79 lks. mkd. ¼ S19 BT.  
Only the stump of one of the original bearing trees remained.

H. W. Lawrence - Dec. 23, 1955 - C.S. File 42/78

-----  
Corner located by proportional measurement.  
Drove a 1¼" iron pipe for ¼ corner, from which  
An 8" Fir bears N.34°W., 2.3 ft. scribed ¼ S18 BT, 1543.  
A 10" Madrone bears S.23°E., 5.4 ft. scribed ¼ S19 BT, 1543.

BLM Dependent resurvey by Arthur R. Rambo, & Francis Simon Cadastral Surveyors under Group No. 2143, surveyed May 2006/Feb. 2007 - (DCSO records, Vol. 55 Page(s) 21688-9)

-----  
The ¼ sec. cor. of secs. 18 and 19, reestablished by proportionate measurement, by Lawrence, in 1955. There is no remaining evidence of the original cor., therefore this position is accepted as the cor.; monumented with an iron pipe, 1¼" dia., firmly set, projecting 12" above the ground, from which a bearing tree mkd. by Lawrence:

A madrone, 23" dia., bears S.23°E., 5.3 ft., with a healed double blaze.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, directly over iron pipe, in a collar of stone, with brass cap mkd.

T32S R5W  
¼ S 18  
S 19  
2006

from which new bearing trees

continued next page

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 140400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 18 and 19

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 12" dia., bears N.44°E., 24.0 ft., mkd. ¼ S18 BT.  
A fir, 11" dia., bears S.76½°E., 25.2 ft., mkd. ¼ S19 BT.  
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail)  
driven at the base right side-center, unless otherwise  
described in the corner description  
Deposit a magnet in a white plastic case at the base of the  
stainless steel post.