

PRIMARY CORNER DESCRIPTION 1/4 Secs. 7 & 18

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Oscar F. Thiel, Deputy Surveyor, under Contract #729, dated Dec. 24, 1900 and special instructions dated Sept. 12, 1901 (DCSO records Vol. 20 Page(s) 8606)

Set a yew post, 3 ft long, 3" sq. 24" in the ground for ¼ sec. cor. mkd ¼ S7 on N & 18 on S face from which

A fir, 40" dia., bears N.79°E., 55 lks., mkd: ¼ S7 BT.

A fir, 10" dia., bears S.8½°E., 30 lks., mkd: ¼ S18 BT.

BLM Dependent resurvey by Arthur R. Rambo, & Francis Simon Cadastral Surveyors under Group No. 2143, surveyed May 2006/Feb. 2007 - (DCSO records, Vol. 55 Page(s) 21692)

Point for the ¼ sec. cor. of secs. 7 and 18, at proportionate dist., there is no remaining evidence of the original cor. Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd.

T32S R5W

¼ $\frac{S \ 7}{S \ 18}$

2006

from which

A fir, 13" dia., bears N.2½°E., 30.6 ft., mkd. ¼ S7 BT.

A fir, 15" dia., bears S.27¼°W., 41.3 ft., mkd. ¼ S18 BT.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

Deposit a magnet in a white plastic case at the base of the stainless steel post.