

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 200100

PRIMARY CORNER DESCRIPTION C C for Secs. 31 and 32 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Oscar F. Thiel, Deputy Surveyor, under Contract #729, dated Dec. 24, 1900 and special instructions dated Sept. 12, 1901 (DCSO records Vol. 20 Page(s) 8601)

Intersect S. bdy. of Tp. 128 lks. W. of cor. of secs. 5, 6, 31 and 32, which is a quartz stone 8 x 10 ins., 3" above ground, marked and witnessed as described by the surveyor general. I destroy the marks referring to secs. 31 and 32, and at the point of intersection I set a dogwood post, 3 ft. long, 4" sq., 24" in the ground, for closing cor. of secs. 31 and 32, marked T32S R5W on N.; S32 on E.; and S31 on W. faces with 5 grooves on E. and 1 groove on W. faces, from which
A Fir 36" dia. bears N.43°E., 57 lks. mkd T32S R5W S32 BT
A Laurel 10" dia., bears N.38°W., 32 lks. marked T32S R5W S31 BT.

George J. Wenderoth, - For: Geo. Newman - 1953 - C.S. 49/112

Found C.C. sec. 32
10" Madrona, N.38°W., 21.1 ft.
36" Fir N.43°E., 37.6 ft., stump scribed
Drive 1" Iron pipe for corner.
Mark - 5" Fir N.36°45'W., 15.0 ft.
6" Fir N.39°30'E., 29.5 ft.

Douglas County Surveyors Office - James Bryon, Deputy - Milo Godfrey, S.A. Bilow, crew - For: C & D Lumber Co. Aug. 1958 -C.S File 49/112 and M 12-51

Found - 1" Iron pipe and BTs as recorded by Wenderoth.
One of Theil's BTs, 10" Laurel N.38°W., 21.1 ft., has open face, good scribing "BT"
Set brass cap alongside 1" I.P. mkd: County Surveyors Office
T 32 S R 5 W
S31 | S32
S 5
1958
I destroy all evidence of standard corner and BTs: $\frac{31}{6} | \frac{32}{5}$
I reset old corner stone alongside brass cap.
New BT - 5" W.Fir S.65°W., 11.6 ft. scribed "CC S31 - 32 CSBT"

Cor. Fd. OK, DCSO, Aug. 1967 C.S. File 53/52-16

Fd ok on BLM dependent resurvey by Terrence O. Nickerson, Cadastral Surveyor under Group #1474 survey Feb. 1989/June 1992 - (DCSO records Vol. 53 Pg(s) 20353-4)

cont.

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 200100

PRIMARY CORNER DESCRIPTION C C for Secs. 31 and 32 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Found OK by M. Hull, Feb. 27, 2004 - M144-18

BLM Dependent resurvey by Arthur R. Rambo, & Francis Simon Cadastral Surveyors under Group No. 2143, surveyed May 2006/Feb. 2007 - (DCSO records, Vol. 55 Page(s) 21680-1)

The closing cor. of secs. 31 & 32, on the S. bdy. of the Tp. monumented with an iron post, 1½" dia. firmly set, projecting 12" above the ground, with brass cap (properly) mkd from which the remains of original bearing trees

A sawed decayed fir stump, 36" dia., bears N.43°E., 37.6 ft., no marks visible.

A root hole with madrone alongside, 14" dia., bears N.38°W., 21.1 ft., no marks visible.

and a bearing tree mkd. by Wenderoth, in 1953, reported by Nickerson in 1989-92 as being marked by the Douglas County Surveyor's Office

A fir, 17" dia., bears N.39½°E., 29.7 ft., with a healed blaze.

and a bearing tree mkd. by Wenderoth, in 1953

A fir, 14" dia., bears N.39½°W., 15.0 ft., with a healed blaze.

and a bearing tree mkd. by the Douglas County Surveyor's Office, in 1958, reported by Nickerson in 1989-92

A fir snag, 8" dia., bears S.65°W., 11.6 ft., with a healed blaze.

A quartz stone 6x8" projecting 4" above the ground, and an iron pipe, 1½" dia., projecting 11" above the ground, are both found alongside the iron post.

(NAD 1983 (CORS 96))

Latitude: 42°44'22.14"N. Longitude: 123°19'39.23"W.

BLM dependent resurvey by Kevin G Mulder, Cadastral Surveyor, under Group No. 3006; Surveyed April 2021/Nov. 2022 - (DCSO records Vol. 59 Page(s) 24117)

The closing cor. of secs. 31 & 32, T32S R5W reported by Rambo & Simon in 2006-07, bears N.89°21'01"W., 83.67 ft; monumented with an iron post, 1½" dia., firmly set, projecting 12" above the ground, with brass cap (properly) mkd from which the remains of BTs reported by Rambo and Simon

A fir, 20" dia., bears N.39½°E., 29.7 ft., with a healed blaze.

A rotted fir stump, 36" dia., bears N.43°E., 37.6 ft., no marks visible. (Original)

A fir, 16" dia., bears N.39½°W., 15.0 ft., with a healed blaze.

Continued next page

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 200100

PRIMARY CORNER DESCRIPTION C C for Secs. 31 and 32 only

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

A quartz stone, 6x8", projecting 4" above the ground, and an iron pipe, 1 1/2" dia., projecting 11" above the ground, are both found alongside the iron post.