

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 31 and 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Oscar F. Thiel, Deputy Surveyor, under Contract #729, dated Dec. 24, 1900 and special instructions dated Sept. 12, 1901 (DCSO records Vol. 20 Page(s) 8602)

Set a Fir post 3 ft. long, 3" sq., 24" in the ground, for 1/4 sec. cor. marked 1/4 S. 31 on W.; and 32 on S. face, from which
A Laurel 9" dia., bears N.24 1/2°E., 30 lks. mkd. 1/4 S32 BT.
A Chinquapin 8" dia., bears N.16°W., 44 lks. mkd. 1/4 S31 BT

W. F. Briggs, Co. Surveyor - Wit: James Levens and W.C. Kennedy - July 26, 1900 - Vol. 2 Page 97

In setting this corner this corner, Briggs makes no mention of any old Witness trees. He just set a post for the corner, from which
A Fir 10" dia., bears N.53°W., 70 lks. (New BT)
A Laurel 8" dia., bears East, 13 lks. (New BT)

Searched for, not found, Aug. 1967, DCSO, John Powell

Survey by Donald Bentz, L.S. #839 - For: Robert Franz - March 24, 1987 - M 101-16

(Set by proportionate measurement)
Set 5/8" x 30" Iron rod with plastic cap mkd. "Bentz Survey Inc."
BTS - 26" Fir N.50°E., 25.4 ft. scribed "1/4 S32 BT"
10" Madrone N.57°W., 11.0 ft. scribed "1/4 S31 BT"

Found OK by G. Nygren, Mar. 2001 - M136-79
Found OK by M. Hull, Feb. 2004 - M144-18

BLM Dependent resurvey by Arthur R. Rambo, & Francis Simon Cadastral Surveyors under Group No. 2143, surveyed May 2006/ Feb. 2007 - (DCSO records, Vol. 55 Page(s) 21680)

The 1/4 sec. cor. of secs. 31 and 32, reestablished by proportionate measurement by Bentz, in 1987 and utilized by various professional land surveyors. There is no remaining evidence of the original cor., therefore this position is accepted as the cor.; monumented with an iron rod, 5/8" dia., firmly set, projecting 6" above the ground, with plastic cap mkd. BENTZ SUR INC., from which bearing trees mkd. by Bentz:
A fir, 31" dia., bears N.51 1/2°E., 24.8 ft., with a healed blaze.
A madrone, 11" dia., bears N.55 3/4°W., 10.9 ft., with scribe marks 1/4 S31 BT visible on a partially healed blaze.

continued next page

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 200140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 31 and 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, directly over iron rod, with brass cap mkd.

T 32 S R 5 W

¼

S 31 | S 32

2006

Deposit a magnet in a white plastic case at the base of the stainless steel post.