

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 29 and 30

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Original - GLO survey by Wells Lake, Deputy Surveyor, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8575)

Set Qr. sec. post, from which
A Cedar 9' dia., bears N.60°E., 8 lks.
A Cherry 5" dia., bears N.51°W., 26 lks.

W.F. Briggs, Co. Surveyor - For: H. Woodford and Ch. Aytch
July 1900 - Vol. 2 Page 97 and Page 263

Set ¼ S. Cor. 29, and 30, the original BT has been destroyed by fir. Made new bearing trees, to wit:
Fir 8" dia., bears S.9°W., 94 lks.
Fir 12" dia., bears S.74½°E., 86 lks.

George J. Wenderoth, Doug. Co. Surveyor - Wit: L. Pureblood
-August 1950 - M 32-2

Found - 8" Fir S.9°W., 62.0 ft.
18" Fir S.74°30'E., 56.7 ft.
Both trees dead, marks showing.
Drive 1/2" I.Pipe.
Scribe - 20" Pine N.75°W., 35.9 ft.
20" Pine S.62°15'W., 77.2 ft.

BLM dependent resurvey by Joseph S. Gawron and Norman J. McDonald, under Group #472, surveyed June/July 1962 (DCSO records Vol. 32 Page(s) 13253-54)

The original ¼ sec. cor. of secs. 29 and 30, perpetuated by the Co. Surveyor in 1900, monumented with an iron pipe, 1/2" dia., firmly set, protruding 9" above the ground, from which
A Fir snag 16" dia., bears S.74½°E., 86 lks. dist., mkd. CS ¼ S29. (Mkd. by Briggs in 1900)
A Fir snag 18" dia., bears S.9°W., 94 lks. dist., mkd. 4 S. (Mkd. by Briggs, in 1900)
A yellow Pine 28" dia., bears N.75°W., 56 lks. dist., with a healed blaze. (Mkd. by County in 1956)
At the corner point
Set an iron post, 30 ins. long, 2 1/2 ins. dia., 22 ins. in the ground, with brass cap marked T 32 S R 5 W
¼
S 30 S 29
1962
from which
A Fir 14" dia., bears S.84°E., 61 lks. mkd. ¼ S29 BT.

(Cont. Next Page)

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 200240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 29 and 30

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

A Fir 8" dia., bears N.81°W., 110 lks. dist., mkd. ¼ S30 BT
Deposit iron pipe alongside the iron post.

Fd. OK, by Max Hull, Sept. 1985, M 99-33 and C.S. File 63/24