

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 19 and 20

Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____
Alias	Description
_____	_____

Original - GLO survey by Wells Lake, Deputy Surveyor, under Contract #54, dated Feb. 19, 1855 (DCSO records Vol. 20 Page(s) 8572)

-----  
Set qr. sec. post on S. slope, from which  
A Y.Pine 12" dia., bears S.57°E., 20 lks.  
A W.Oak 8" dia., bears N.12°W., 24 lks.

C. E. Roberts - For: P. H. Springer - Sept. 16, 1904 - Vol. 2 Page 135 and Field Book 9 Page 4

-----  
Relocated obliterated quarter cor. bet. 19 and 20 midway bet. its corresponding sec. cors. A post marked ¼ S on N. side and C.S. on S. side, from which  
A B.Oak 32" bears S.29°W., 48 lks.  
A B.Oak 18" bears N.51°E., 57 lks.

H.L. Eppstein - Wit: N.E. Richardson, John Ogden - July 18, 1939 - (no record source found - see "old" corner book, page 171)

-----  
Corner located from the original BT, namely  
A 32" B.Oak S.29°W., 48 lks. Tree in good condition, now 48" dia..  
Post for corner, and marked new BT:  
A Fir 10" dia., bears N.62½°E., 26.0 ft. blazed and scribed ¼ S CS BT.

George J. Wenderoth, D.C.S. - Wit: L. Pureblood - 1950-51-52 - M 27-12; M 8-25

-----  
5/8" Iron rod.  
32" B.Oak S.29°W., 31.7 ft.  
10" Fir N.62°30'E., 26.0 ft.

BLM dependent resurvey by Joseph S. Gawron and Norman J. McDonald, under Group #472, surveyed June/July 1962 (DCSO records Vol. 32 Page(s) 13255)

-----  
The ¼ sec. cor. of 19 and 20, determined from bearing trees recorded by the County Surveyor (Briggs) in 1900 (??)  
A down Fir bears N.62½°E., 39 lks. mkd. ¼ S BT.  
A B.Oak 33" dia., bears S.29°W., 48 lks. mkd. S BT.  
At the corner point  
Set an iron post, 30 ins. long, 2 1/2 ins. dia., 26 ins. in the ground, with brass cap marked  
(Cont. Next Page)

TOWNSHIP 32 RANGE 05 POINT IDENTIFIER # 200340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 19 and 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>T 32 S R 5 W <math>\frac{1}{4}</math> S 19*S 20 1962</p> <p>from which A Fir 15" dia., bears S.84<math>\frac{1}{2}</math>°E., 181 lks. dist., mkd. <math>\frac{1}{4}</math> S20 BT. A Yellow Pine 12" dia., bears S.79<math>\frac{1}{2}</math>°W., 89 lks. dist., mkd. <math>\frac{1}{4}</math> S19 BT.</p>
<p>Cor. Fd. OK, Max Hull, Sept. 1985, M 99-33 and C.S. File 63/24</p> <p>Fd. Ok by Raymond Brown 2/2003 - M141-73</p>
<p>BLM Dependent resurvey by Arthur R. Rambo, &amp; Francis Simon Cadastral Surveyors under Group No. 2143, surveyed May 2006/Feb. 2007 - (DCSO records, Vol. 55 Page(s) 21685)</p> <p>-----</p> <p>The <math>\frac{1}{4}</math> sec. cor. of secs. 19 and 20, monumented with an iron post, 2<math>\frac{1}{2}</math>" dia., firmly set, projecting 10" above the ground, with brass cap (properly) mkd. from which a bearing tree mkd. by the Douglas County Surveyor's Office in 1904, reported by Gawron and McDonald as being mkd. by the Douglas County Surveyor's Office in 1900 A root hole, bears S.29°W., 31.7 ft. and bearing trees mkd. by Gawron and McDonald A fir, 23" dia., bears S.84<math>\frac{1}{2}</math>°E., 119.5 ft., with a healed blaze. A pine, 23" dia., bears S.79<math>\frac{1}{2}</math>°W., 58.7 ft., with a healed blaze.</p>
<p>2</p>